

屋内照明器具特性

品番 (品名)	XS Z B 8 3 3 1 4									
光源	LLD2401LCB1 ×1					500.0 l m				
管理番号	K0193686 (0) DB 1									
B Z 分類	BZ2 / 1.8 / BZ3 / 8.5 / BZ4									

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束	9 % 84 %	室指数	照明率 (X0.01)																ZCM		
保守率	良 中 否 0.63 0.6 0.56	0.6	61	52	46	42	59	51	46	42	57	49	45	41	54	48	44	41	39		
		0.8	69	60	55	51	67	59	54	50	64	57	53	49	61	56	52	48	46		
		1.0	74	66	61	57	72	65	60	56	69	63	58	55	66	61	57	54	51		
		1.25	78	71	66	62	76	70	65	61	73	67	63	60	69	65	61	59	56		
下方投影面積 等価発光面積	c m ² c m ²	1.5	81	75	70	66	79	74	69	65	75	71	67	64	72	68	65	62	59		
		2.0	85	80	76	72	83	78	74	71	79	75	72	69	76	72	70	67	64		
取付 高さ	器具間隔最大限		2.5	88	83	79	76	85	81	78	75	81	78	75	73	78	75	73	71	67	
	横方向 (A) H m	縦方向 (B) H m	3.0	89	85	82	79	87	84	80	78	83	80	78	75	79	77	75	73	69	
			4.0	91	88	85	83	89	86	84	81	85	83	81	79	81	79	78	76	72	
			5.0	93	90	88	85	90	88	86	84	86	84	83	81	83	81	80	78	74	
			7.0	94	92	90	89	92	90	88	87	88	86	85	84	84	83	82	81	76	
			10.0	95	94	92	91	93	92	91	89	89	88	87	86	85	84	84	83	78	

