

屋内照明器具特性

品番 (品名)	XS Z B 8 3 3 1 7				
光源	LLD2401VCB1 ×1 500.0 l m				
管理番号	K0193060 (0) DB 1				
B Z 分類	B Z 6				

器具効率	82 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		25 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		57 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			Z C M	
保守率	良	0.63	0.6	4.2	3.2	2.6	2.1	4.0	3.1	2.5	2.1	3.5	2.8	2.3	1.9	3.1	2.5	2.1	1.8	1.5	
	中	0.6	0.8	4.9	3.9	3.3	2.8	4.6	3.7	3.1	2.7	4.1	3.4	2.9	2.5	3.6	3.1	2.6	2.3	1.9	
	否	0.56	1.0	5.4	4.4	3.8	3.3	5.1	4.2	3.6	3.2	4.5	3.8	3.3	2.9	4.0	3.4	3.0	2.7	2.2	
			1.25	5.8	5.0	4.3	3.8	5.5	4.7	4.1	3.7	4.9	4.2	3.8	3.4	4.3	3.8	3.4	3.1	2.6	
下方投影面積	c m ²		1.5	6.1	5.3	4.7	4.2	5.8	5.1	4.5	4.1	5.1	4.6	4.1	3.7	4.6	4.1	3.7	3.4	2.8	
等価発光面積	c m ²		2.0	6.6	5.9	5.3	4.8	6.2	5.6	5.1	4.6	5.5	5.0	4.6	4.3	4.9	4.5	4.2	3.9	3.2	
取付高さ	器具間隔最大限		2.5	6.8	6.2	5.7	5.3	6.5	5.9	5.5	5.1	5.8	5.4	5.0	4.6	5.2	4.8	4.5	4.2	3.5	
	横方向 (A)	縦方向 (B)	3.0	7.1	6.5	6.0	5.6	6.7	6.2	5.8	5.4	6.0	5.6	5.2	4.9	5.3	5.0	4.7	4.5	3.8	
H m	0.94 H m	0.94 H m	4.0	7.3	6.9	6.5	6.1	7.0	6.5	6.2	5.9	6.2	5.9	5.6	5.4	5.6	5.3	5.1	4.9	4.1	
			5.0	7.5	7.1	6.8	6.4	7.1	6.8	6.5	6.2	6.4	6.1	5.9	5.6	5.7	5.5	5.3	5.1	4.3	
			7.0	7.7	7.4	7.1	6.9	7.3	7.1	6.8	6.6	6.6	6.4	6.2	6.0	5.9	5.8	5.6	5.4	4.6	
			10.0	7.9	7.6	7.4	7.2	7.5	7.3	7.1	6.9	6.8	6.6	6.5	6.3	6.1	6.0	5.8	5.7	4.8	

