

屋内照明器具特性

品番 (品名)	XS Z B 8 3 3 1 8	
光源	LLD2421LCB1 ×1	500.0 l m
管理番号	K0193692 (0) DB 1	
B Z 分類	BZ1 / 1. 1 / BZ2 / 3. 5 / BZ3	

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 9 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	84 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X 0. 0 1)																			Z C M
保守率	良 0. 6 3	0. 6	0. 6	66	58	53	50	65	58	53	50	63	56	52	49	60	55	51	49	47
	中 0. 6	0. 6	0. 8	73	65	60	57	71	65	60	56	68	63	59	56	66	61	58	55	53
	否 0. 5 6	0. 6	1. 0	77	70	65	62	75	69	65	61	72	67	63	60	69	65	62	59	57
下方投影面積 等価発光面積	c m ²	1. 2 5	81	75	70	66	79	73	69	66	76	71	67	64	73	69	66	63	60	
		1. 5	83	78	73	70	81	76	72	69	78	74	70	68	75	71	69	66	63	
取付 高さ	器具間隔最大限		2. 5	87	82	78	75	85	80	77	74	81	78	75	72	78	75	72	70	67
	横方向 (A)	縦方向 (B)	3. 0	89	85	81	78	87	83	80	77	83	80	77	75	80	77	75	73	70
H m	0. 4 8 H m	0. 5 1 H m	4. 0	90	87	83	81	88	85	82	80	84	82	79	77	81	79	77	75	71
			5. 0	92	89	87	84	90	87	85	83	86	84	82	80	83	81	79	78	74
			7. 0	93	91	88	86	91	89	87	85	87	86	84	82	84	82	81	80	75
			10. 0	95	93	91	89	93	91	89	88	89	87	86	85	85	84	83	82	77
				96	94	93	91	94	92	91	90	90	89	88	87	86	85	84	84	79

