

屋内照明器具特性

品番 (品名)	XS Z B 8 3 3 1 9																	
光源	LLD2421VCB1 ×1									500.0 1 m								
管理番号	K0193692 (0) DB 1																	
BZ分類	BZ1 / 1.1 / BZ2 / 3.5 / BZ3																	

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %					
	上方光束		9 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
	下方光束		84 %		床	10 %				10 %				10 %				10 %				0 %		
室指数	照明率 (X 0.01) ZCM																							
保守率	良	0.63	0.6	0.56	0.6	66	58	53	50	65	58	53	50	63	56	52	49	60	55	51	49	47		
	中	0.6	0.6	0.56	0.8	73	65	60	57	71	65	60	56	68	63	59	56	66	61	58	55	53		
	否	0.56	0.56	0.56	1.0	77	70	65	62	75	69	65	61	72	67	63	60	69	65	62	59	57		
下方投影面積 等価発光面積	c m ²	1.25	1.5	2.0	2.5	81	75	70	66	79	73	69	66	76	71	67	64	73	69	66	63	60		
		1.5	2.0	2.5	3.0	83	78	73	70	81	76	72	69	78	74	70	68	75	71	69	66	63		
		2.0	2.5	3.0	4.0	87	82	78	75	85	80	77	74	81	78	75	72	78	75	72	70	67		
取付高さ	器具間隔最大限		H m	0.48 H m	縦方向 (B)	0.51 H m	H m	0.51 H m	H m	0.51 H m	H m	0.51 H m	H m	0.51 H m	H m	0.51 H m	H m	0.51 H m	H m	0.51 H m	H m	0.51 H m	H m	0.51 H m
	横方向 (A)	縦方向 (B)																						

