

# 屋内照明器具特性

品番 (品名)	XS Z D 1 0 0 1 V	
光源	LLD2401VCB1 ×1	500.0 l m
管理番号	K0191442 ( 0 ) DB 1	
B Z 分類	B Z 2 / 8 . 5 / B Z 1	

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	89 %	室指数	照明率 ( X 0 . 0 1 )																				Z C M
保守率	良	0.67	0.6	60	52	46	42	59	51	46	42	58	50	45	42	56	50	45	42	40			
	中	0.63	0.8	70	62	57	53	69	61	57	53	67	60	56	53	65	60	56	52	51			
	否	0.56	1.0	75	69	64	60	74	68	63	60	72	67	63	60	70	66	62	59	58			
			1.25	80	74	70	66	79	73	69	66	77	72	69	66	75	71	68	65	64			
下方投影面積		cm <sup>2</sup>	1.5	83	78	74	70	82	77	73	70	79	75	72	70	78	74	71	69	67			
等価発光面積		cm <sup>2</sup>	2.0	86	82	79	76	85	81	78	76	83	80	77	75	81	78	76	74	72			
取付高さ	器具間隔最大限		2.5	88	85	82	80	87	84	82	79	85	83	80	78	83	81	79	77	76			
	横方向 ( A )	縦方向 ( B )	3.0	90	87	84	82	89	86	84	82	87	84	82	81	85	83	81	80	78			
H m	1.25 H m	1.25 H m	4.0	92	89	87	85	91	88	87	85	88	87	85	84	86	85	84	83	80			
			5.0	93	91	89	88	92	90	88	87	89	88	87	86	88	86	85	84	82			
			7.0	94	92	91	90	93	91	90	89	91	90	89	88	89	88	87	86	84			
			10.0	95	94	93	92	94	93	92	91	92	91	90	89	90	89	88	88	85			

