

屋内照明器具特性

品番 (品名)	XS Z D 1 0 6 2 V	
光源	LLD2410VCB1 ×1	500.0 l m
管理番号	K0192028 (0) DB 1	
B Z 分類	B Z 1	

器具効率	84 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	84 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0 . 0 1)																			Z C M
保守率	良	0.67	0.6	78	75	72	71	78	74	72	71	77	74	72	71	76	74	72	71	70
	中	0.63	0.8	81	78	76	75	81	78	76	75	80	77	76	74	79	77	75	74	73
	否	0.56	1.0	83	81	79	77	83	80	78	77	82	80	78	77	81	79	78	76	76
下方投影面積	等価発光面積	c m ²	1.25	85	83	81	79	84	82	80	79	83	81	80	79	82	81	79	78	77
			1.5	86	84	82	81	85	83	82	81	84	82	81	80	83	82	80	80	78
取付高さ	器具間隔最大限		2.5	88	87	85	84	87	86	85	84	86	85	84	83	84	84	83	82	81
	横方向 (A)	縦方向 (B)	3.0	89	87	86	85	88	87	86	85	86	85	85	84	85	84	83	83	81
H m	0.80 H m	0.80 H m	4.0	89	88	87	87	88	88	87	86	87	86	85	85	85	85	84	84	82
			5.0	90	89	88	88	89	88	87	87	87	87	86	86	86	85	85	84	82
			7.0	90	90	89	89	89	88	88	88	87	87	86	86	86	85	85	83	
			10.0	91	90	90	89	90	89	89	88	88	88	87	87	86	86	86	83	

