

屋内照明器具特性

品番 (品名)	XS Z D 1 0 6 4 L	
光源	LLD2411LCB1 ×1	500.0 l m
管理番号	K0192034 (0) DB 1	
B Z 分類	B Z 1	

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	83 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0 . 0 1)																			Z C M
保守率	良	0.67	0.6	77	74	72	70	77	73	71	70	76	73	71	70	75	73	71	70	69
	中	0.63	0.8	80	77	75	74	80	77	75	74	79	76	75	73	78	76	74	73	73
	否	0.56	1.0	82	80	78	76	82	79	78	76	81	79	77	76	80	78	77	76	75
下方投影面積	等価発光面積	c m ²	1.25	84	82	80	78	83	81	80	78	82	80	79	78	81	80	78	77	76
			1.5	85	83	81	80	84	82	81	80	83	81	80	79	82	81	79	79	77
取付高さ	器具間隔最大限		2.5	87	86	84	83	86	85	84	83	85	84	83	82	83	83	82	81	80
	横方向 (A)	縦方向 (B)	3.0	88	86	85	84	87	86	85	84	85	84	84	83	84	83	82	82	80
H m	0.80 H m	0.80 H m	4.0	88	87	86	86	87	87	86	85	86	85	84	84	84	84	83	83	81
			5.0	89	88	87	86	88	87	86	86	86	86	85	85	85	84	84	83	81
			7.0	89	89	88	88	88	88	87	87	87	86	86	85	85	85	84	84	82
			10.0	90	89	89	88	89	88	88	88	87	87	86	86	85	85	85	85	82

