

屋内照明器具特性	
品番 (品名)	XND9 9 8 9 S L Z
光源	LED3000_80_11765 ×1 11765.0 lm
管理番号	K0188513 (0) DB 1
B Z 分類	BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																					Z C M
下方光束				1 0 0 %																					
保守率		良 中 否	0 . 7 6	0 . 6	7 4	6 6	6 1	5 7	7 3	6 5	6 0	5 7	7 2	6 5	6 0	5 7	7 0	6 4	6 0	5 7	5 5				
			0 . 7 2	0 . 8	8 3	7 6	7 1	6 8	8 2	7 6	7 1	6 8	8 0	7 5	7 1	6 7	7 9	7 4	7 0	6 7	6 6				
			1 . 0	8 9	8 3	7 8	7 5	8 8	8 2	7 8	7 5	8 6	8 1	7 7	7 4	8 4	8 0	7 6	7 4	7 2					
			0 . 6 4	1 . 2 5	9 3	8 8	8 4	8 1	9 2	8 7	8 3	8 0	9 0	8 6	8 2	8 0	8 8	8 5	8 2	7 9	7 8				
下方投影面積		c m ²	1 . 5	9 6	9 1	8 7	8 4	9 5	9 0	8 7	8 4	9 3	8 9	8 6	8 3	9 1	8 7	8 5	8 3	8 1					
等価発光面積			c m ²	2 . 0	9 9	9 5	9 2	9 0	9 8	9 4	9 2	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 7	8 6				
取付 高さ	器具間隔最大限		2 . 5	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 8	9 5	9 3	9 1	9 6	9 4	9 2	9 0	8 8					
	横方向 (A) 縦方向 (B)		3 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 4	9 2	9 0					
H m	1 . 3 1 H m	1 . 3 1 H m	4 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 1	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 3					
			5 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4					
			7 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	1 0 0	9 9	9 8	9 6					
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 7					

