

屋内照明器具特性

品番 (品名)	XS Z D 1 0 6 7 V	
光源	LLD2410VCB1 ×1	500.0 l m
管理番号	K0192040 (0) DB 1	
B Z 分類	B Z 1	

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	86 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0 . 0 1)																			Z C M
保守率	良	0.67	0.6	77	74	71	69	77	73	71	69	76	73	71	69	75	72	70	69	68
	中	0.63	0.8	81	78	75	74	81	77	75	74	80	77	75	73	79	76	74	73	72
	否	0.56	1.0	84	81	78	77	83	80	78	76	82	79	78	76	81	79	77	76	75
下方投影面積	等価発光面積	c m ²	1.25	86	83	81	79	85	82	80	79	84	81	80	78	82	81	79	78	77
			1.5	87	84	82	81	86	84	82	81	85	83	81	80	83	82	81	79	78
取付高さ	器具間隔最大限		2.5	89	88	86	85	89	87	86	84	87	86	85	84	85	84	84	83	81
	横方向 (A)	縦方向 (B)	3.0	90	89	87	86	89	88	87	86	87	86	85	85	86	85	84	84	82
H m	0.80 H m	0.80 H m	4.0	91	90	89	88	90	89	88	87	88	87	87	86	87	86	85	85	83
			5.0	91	90	89	89	90	90	89	88	89	88	87	87	87	86	86	85	85
			7.0	92	91	90	90	91	90	90	89	89	89	88	88	87	87	86	84	84
			10.0	92	92	91	91	91	91	90	90	89	89	89	88	88	87	87	87	85

