

屋内照明器具特性	
品番 (品名)	XS Z D 1 0 6 9 V
光源	L L D 2 4 1 1 V C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 2 0 4 6 (0) D B 1
B Z 分類	B Z 1

器具効率		8 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		8 1 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良	0 . 6 7	0 . 6	7 4	7 1	6 9	6 7	7 4	7 1	6 9	6 7	7 3	7 0	6 9	6 7	7 2	7 0	6 8	6 7	6 7
		中	0 . 6 3	0 . 8	7 8	7 5	7 3	7 1	7 7	7 4	7 2	7 1	7 6	7 4	7 2	7 1	7 5	7 3	7 2	7 1	7 0
		否	0 . 5 6	1 . 0	8 0	7 7	7 5	7 4	7 9	7 7	7 5	7 4	7 8	7 6	7 4	7 3	7 7	7 5	7 4	7 3	7 2
				1 . 2 5	8 1	7 9	7 7	7 6	8 1	7 8	7 7	7 6	7 9	7 8	7 6	7 5	7 8	7 7	7 6	7 5	7 4
下方投影面積		c m ²	1 . 5	8 2	8 0	7 9	7 7	8 2	8 0	7 8	7 7	8 0	7 9	7 7	7 6	7 9	7 8	7 7	7 6	7 5	
等価発光面積			c m ²	2 . 0	8 4	8 2	8 0	7 9	8 3	8 1	8 0	7 9	8 1	8 0	7 9	7 8	8 0	7 9	7 8	7 8	7 6
取付	器具間隔最大限			2 . 5	8 4	8 3	8 2	8 1	8 4	8 2	8 1	8 0	8 2	8 1	8 0	7 9	8 1	8 0	7 9	7 9	7 7
高さ	横方向 (A)		縦方向 (B)	3 . 0	8 5	8 4	8 3	8 2	8 4	8 3	8 2	8 1	8 3	8 2	8 1	8 0	8 1	8 0	8 0	7 9	7 8
H m	0 . 8 0 H m		0 . 8 0 H m	4 . 0	8 5	8 4	8 4	8 3	8 5	8 4	8 3	8 2	8 3	8 2	8 2	8 1	8 2	8 1	8 1	8 0	7 8
				5 . 0	8 6	8 5	8 4	8 4	8 5	8 4	8 4	8 3	8 3	8 3	8 2	8 2	8 2	8 1	8 1	8 1	7 9
				7 . 0	8 6	8 6	8 5	8 5	8 5	8 5	8 4	8 4	8 4	8 3	8 3	8 3	8 2	8 2	8 2	8 1	7 9
				1 0 . 0	8 7	8 6	8 6	8 5	8 6	8 5	8 5	8 5	8 4	8 4	8 3	8 3	8 2	8 2	8 2	8 2	8 0

