

屋内照明器具特性

品番 (品名)	XS Z D 3 0 6 0 L	
光源	LLD3410LCB1 ×1	700.0 1 m
管理番号	K0191488 (0) DB 1	
B Z 分類	B Z 1	

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束 0 %		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	99 %	床		10 %				10 %				10 %				10 %				0 %			
室指数	照明率 (X 0 . 0 1)																			Z C M			
保守率	良 0.67	0.6	0.6	89	84	81	79	88	84	81	79	87	83	81	79	86	83	81	79	78			
	中 0.63		0.8	93	89	86	84	92	89	86	84	91	88	86	84	90	87	85	84	83			
	否 0.56		1.0	96	92	90	88	95	92	89	87	94	91	89	87	92	90	88	87	86			
下方投影面積	c m ²	等価発光面積	c m ²	1.25	98	95	92	90	97	94	92	90	96	93	91	90	94	92	91	89	88		
				1.5	100	97	94	93	99	96	94	92	97	95	93	92	96	94	92	91	90		
取付高さ	器具間隔最大限		H m	0.80 H m	0.80 H m	2.5	103	100	99	97	102	100	98	97	100	98	97	96	98	97	96	95	93
	横方向 (A)	縦方向 (B)				3.0	103	102	100	99	102	101	99	98	100	99	98	97	99	98	97	96	94
H m	0.80 H m	0.80 H m	4.0	104	103	102	101	103	102	101	100	101	100	99	98	99	99	98	97	95			
			5.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	99	98	96			
			7.0	105	105	104	103	104	104	103	102	102	102	101	100	100	99	99	97				
10.0	106	105	105	104	105	104	104	103	103	102	102	102	101	100	100	100	97						

