

# 屋内照明器具特性

品番 (品名)	XS Z D 3 0 6 1 V	
光源	LLD3411VCB1 ×1	700.0 1 m
管理番号	K0191445 (0) DB 1	
BZ分類	BZ1	

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	94 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X 0.01 )																			ZCM
保守率	良	0.67	0.6	83	79	76	74	83	79	76	74	82	78	75	74	81	77	75	73	73
	中	0.63	0.8	88	84	81	79	87	83	81	79	86	83	80	79	85	82	80	78	77
	否	0.56	1.0	91	87	84	82	90	87	84	82	89	86	83	82	87	85	83	81	80
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	93	90	87	85	92	89	87	85	91	88	86	85	89	87	86	84	83
			1.5	94	91	89	87	94	91	89	87	92	90	88	87	91	89	87	86	85
取付高さ	器具間隔最大限		2.5	97	95	94	92	96	95	93	92	95	93	92	91	93	92	91	90	88
	横方向 (A)	縦方向 (B)	3.0	98	96	95	94	97	96	94	93	95	94	93	92	94	93	92	91	89
Hm	0.83 Hm	0.83 Hm	4.0	99	98	97	95	98	97	96	95	96	95	94	93	94	94	93	92	90
			5.0	100	98	98	97	99	98	97	96	97	96	95	94	95	94	94	93	91
			7.0	100	99	99	98	99	98	98	97	97	97	96	96	95	95	94	94	92
			10.0	100	100	100	99	100	99	99	98	98	97	97	96	96	95	95	95	92

