

# 屋内照明器具特性

品番 (品名)	XS Z D 3 0 6 5 L	
光源	LLD3411LCB1 ×1	700.0 1m
管理番号	K0192049 (0) DB 1	
BZ分類	BZ1	

器具効率	81 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	81 %	床	10 %				10 %				10 %				10 %				0 %		
室指数	照明率 ( X 0.01 )																				ZCM
保守率	良	0.67	0.6	75	71	69	68	74	71	69	68	74	71	69	68	73	70	69	68	67	
	中	0.63	0.8	78	75	73	72	78	75	73	72	77	74	73	71	76	74	72	71	70	
	否	0.56	1.0	80	77	75	74	79	77	75	74	78	76	75	74	77	76	74	73	72	
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	82	79	78	76	81	79	77	76	80	78	77	76	79	77	76	75	74	
			1.5	83	80	79	78	82	80	79	77	81	79	78	77	80	78	77	76	75	75
取付高さ	器具間隔最大限		2.0	84	82	81	80	83	82	80	79	82	81	79	79	81	79	79	78	77	
	横方向 (A)	縦方向 (B)	2.5	85	83	82	81	84	83	81	81	82	81	80	80	81	80	80	79	77	
Hm	0.80Hm	0.80Hm	3.0	85	84	83	82	84	83	82	81	83	82	81	80	81	81	80	80	78	
			4.0	86	85	84	83	85	84	83	83	83	83	83	82	82	82	81	81	80	79
			5.0	86	85	85	84	85	85	84	83	84	83	83	82	82	82	81	81	79	
			7.0	87	86	86	85	86	85	85	84	84	84	83	83	83	82	82	82	80	
			10.0	87	87	86	86	86	86	85	85	84	84	84	84	83	83	82	82	80	

