

屋内照明器具特性	
品番 (品名)	XND1038SLK
光源	LED3000_85_930 ×1 930.0 l m
管理番号	K0176469 (0) DB 1
BZ分類	BZ1

器具効率		101 %	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
上方光束		0 %	室指数	照明率 (X0.01)																Z	C	M
下方光束		101 %																				
保守率		良	0.6	78	70	65	62	77	70	65	62	75	69	65	62	74	68	64	62	60		
		中	0.8	86	79	74	71	85	79	74	71	83	78	74	71	81	77	73	71	69		
		否	0.77	1.0	90	85	80	77	89	84	80	77	88	83	79	77	86	82	79	76	75	
		0.68	1.25	94	89	85	82	93	89	85	82	91	87	84	82	90	86	83	81	80		
下方投影面積		c m ²	1.5	97	92	89	86	96	92	88	86	94	90	87	85	92	89	86	84	83		
			2.0	100	96	93	91	99	96	93	90	97	94	92	90	95	93	91	89	87		
等価発光面積		c m ²	2.5	102	99	96	94	101	98	96	94	99	96	94	92	97	95	93	91	90		
			3.0	103	100	98	96	102	100	97	96	100	98	96	94	98	96	95	93	91		
H	m	0.75 H	4.0	105	103	101	99	103	102	100	98	101	100	98	97	99	98	97	96	93		
			5.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95		
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	100	99	96		
			10.0	107	106	105	105	106	105	104	104	104	103	102	102	102	101	101	100	97		

