

屋内照明器具特性	
品番 (品名)	XND9995SVZ
光源	LED3500_80_15995 ×1 15995.0 lm
管理番号	K0188258 (2) DB 1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束		0 %	室指数	照明率 (X0.01)																				ZCM	
下方光束				100 %																					
保守率		良 中 否	0.76	0.6	74	66	61	57	73	65	60	57	72	65	60	57	70	64	60	57	55				
			0.72	0.8	83	76	71	68	82	76	71	68	81	75	71	67	79	74	70	67	66				
			0.64	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	76	74	72				
				1.25	93	88	84	81	92	87	83	80	90	86	82	80	88	85	82	79	78				
下方投影面積		cm ²	1.5	96	91	87	84	95	90	87	84	93	89	86	83	91	87	85	83	81					
等価発光面積			cm ²	2.0	99	95	92	90	98	94	92	89	96	93	90	88	94	91	89	87	86				
取付高さ	器具間隔最大限			2.5	101	98	95	93	100	97	95	92	98	95	93	91	96	94	92	90	88				
横方向 (A)		縦方向 (B)		3.0	102	100	97	95	101	99	97	95	99	97	95	93	97	95	94	92	90				
Hm	1.37Hm	1.37Hm	4.0	104	102	100	98	103	101	99	98	101	99	98	96	99	97	96	95	93					
			5.0	105	103	102	100	104	102	101	99	102	100	99	98	99	98	97	96	94					
			7.0	106	105	103	102	105	104	103	102	103	102	101	100	100	100	99	98	96					
			10.0	107	106	105	104	106	105	104	103	103	103	102	101	101	101	100	100	97					

