

屋内照明器具特性

品番 (品名)	XS Z P 3 3 8 7 L	
光源	LLD3401LCB1+LLD3421LCB1 ×1 1400.0 1m	
管理番号	K0192022 (0) DB 1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 50%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	50%	床		10%				10%				10%				10%				0%
室指数	照明率 (X 0.01)																			ZCM
保守率	良	0.69	0.6	62	54	48	44	59	51	46	43	52	47	43	40	46	42	39	37	33
	中	0.67	0.8	69	61	56	52	65	58	53	50	57	52	49	46	50	47	44	42	36
	否	0.63	1.0	74	67	61	57	69	63	59	55	61	56	53	50	53	50	48	46	38
下方投影面積 等価発光面積	c m ²	1.25	78	72	67	63	73	68	63	60	64	60	57	54	55	53	51	49	40	
		1.5	81	75	71	67	76	71	67	64	66	63	60	57	57	55	53	51	42	
取付高さ	器具間隔最大限		2.5	87	83	80	77	82	78	75	72	71	68	66	64	61	59	58	56	45
	横方向 (A)	縦方向 (B)	3.0	89	85	82	79	83	80	77	75	72	70	68	66	62	60	59	58	46
H m	0.40 H m	0.40 H m	4.0	91	88	86	83	85	83	80	79	74	72	70	69	63	62	61	60	47
			5.0	92	90	88	86	86	84	82	81	75	73	72	71	64	63	62	61	47
			7.0	94	92	90	89	88	86	85	83	76	75	74	73	65	64	63	63	48
			10.0	95	94	92	91	89	88	87	86	77	76	75	75	65	65	64	64	48

