

屋内照明器具特性	
品番 (品名)	XSZR1061N
光源	LLD2411NCB1 ×1 500.0 l m
管理番号	K0192058 (0) DB 1
BZ分類	BZ1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		88 %																							
保守率		良	0.63	0.6	69	62	58	56	68	62	58	55	67	61	58	55	65	61	58	55	54				
		中	0.6	0.8	75	70	66	63	75	69	66	63	73	69	65	63	72	68	65	63	62				
		否	1.0	79	74	71	68	79	74	71	68	77	73	70	68	76	72	69	67	66					
		0.56	1.25	83	78	75	73	82	78	75	72	80	77	74	72	79	76	73	71	70					
下方投影面積		c m ²		1.5	85	81	78	76	84	80	78	75	82	79	77	75	81	78	76	74	73				
				2.0	87	84	82	80	87	84	81	79	85	82	80	79	83	81	79	78	76				
取付高さ	器具間隔最大限			2.5	89	86	84	82	88	86	84	82	86	84	83	81	85	83	81	80	79				
	横方向 (A)		縦方向 (B)	3.0	90	88	86	84	89	87	85	84	87	86	84	83	85	84	83	82	80				
H m	0.74 H m		0.74 H m	4.0	91	90	88	87	90	89	87	86	88	87	86	85	87	86	85	84	82				
				5.0	92	91	89	88	91	90	89	88	89	88	87	86	87	87	86	85	83				
				7.0	93	92	91	90	92	91	90	89	90	89	89	88	88	88	87	86	84				
				10.0	94	93	92	92	93	92	91	91	91	90	90	89	89	88	88	88	85				

