

屋内照明器具特性	
品番 (品名)	XSZR3060N
光源	LLD3410NCB1 ×1 700.0 lm
管理番号	K0192055 (0) DB 1
BZ分類	BZ1

器具効率		90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		90 %																						
保守率		良	0.63	0.6	70	63	59	56	69	63	59	56	68	62	58	56	66	61	58	56	54			
		中	0.6	0.8	77	71	67	64	76	70	66	64	74	69	66	63	73	69	66	63	62			
		否	1.0	81	75	72	69	80	75	71	69	78	74	71	68	77	73	70	68	67				
		0.56	1.25	84	80	76	73	83	79	76	73	81	78	75	73	80	77	74	72	71				
下方投影面積		c m ²		1.5	86	82	79	77	85	82	79	76	83	80	78	76	82	79	77	75	74			
等価発光面積		c m ²		2.0	89	86	83	81	88	85	83	81	86	84	82	80	84	82	81	79	77			
取付	器具間隔最大限			2.5	91	88	86	84	90	87	85	83	88	86	84	82	86	84	83	81	80			
高さ	横方向 (A)		縦方向 (B)	3.0	92	89	87	86	91	89	87	85	89	87	85	84	87	86	84	83	81			
H m	0.75 H m		0.75 H m	4.0	93	91	90	88	92	90	89	88	90	89	88	86	88	87	86	85	83			
				5.0	94	92	91	90	93	92	90	89	91	90	89	88	89	88	87	87	84			
				7.0	95	94	93	92	94	93	92	91	92	91	90	90	90	89	89	88	86			
				10.0	95	95	94	93	94	94	93	92	92	92	91	91	91	90	90	89	87			

