

屋内照明器具特性	
品番 (品名)	XND3538SN
光源	LED5000_80_4130 x1 4130.0lm
管理番号	K0179573(0)DB1
BZ分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %	床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
下方光束		1 0 0 %		照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6	7 5	6 7	6 2	5 8	7 4	6 6	6 1	5 8	7 2	6 6	6 1	5 8	7 1	6 5	6 1	5 8	5 6	
			0 . 7 2	8 3	7 6	7 1	6 8	8 2	7 6	7 1	6 8	8 0	7 5	7 0	6 7	7 9	7 4	7 0	6 7	6 6	
			1 . 0	8 8	8 2	7 7	7 4	8 7	8 1	7 7	7 4	8 5	8 0	7 6	7 3	8 4	7 9	7 6	7 3	7 2	
			0 . 6 4	1 . 2 5	9 3	8 7	8 3	8 0	9 1	8 6	8 2	7 9	8 9	8 5	8 2	7 9	8 7	8 4	8 1	7 8	7 7
下方投影面積		c m ²	1 . 5	9 5	9 0	8 7	8 4	9 4	9 0	8 6	8 3	9 2	8 8	8 5	8 3	9 0	8 7	8 4	8 2	8 0	
			2 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	9 0	8 8	9 3	9 1	8 9	8 7	8 5	
取付 高さ	器具間隔最大限		2 . 5	1 0 1	9 7	9 5	9 2	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 8	
	横方向 (A)	縦方向 (B)	3 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	9 0	
H m	0 . 7 3 H m	0 . 7 3 H m	4 . 0	1 0 4	1 0 1	1 0 0	9 8	1 0 3	1 0 0	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 4	9 2	
			5 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 7	9 9	9 8	9 7	9 6	9 4	
			7 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 9	9 8	9 5	
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 7	

