

屋内照明器具特性	
品番 (品名)	XNN1031PE
光源	LED3000_85_535 x1 535.0 lm
管理番号	K0192368 (0) DB1
BZ分類	BZ5/0.7/BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %					
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %					
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %					
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M			
下方光束				1 0 0 %																						
保守率		良 中 否	0 . 8 3	0 . 6	5 8	4 7	3 9	3 4	5 7	4 6	3 9	3 4	5 5	4 5	3 8	3 3	5 3	4 4	3 8	3 3	3 1					
			0 . 8 1	0 . 8	6 9	5 8	5 0	4 4	6 7	5 7	5 0	4 4	6 5	5 5	4 9	4 4	6 2	5 4	4 8	4 4	4 2					
			0 . 7 7	1 . 0	7 5	6 5	5 8	5 2	7 4	6 4	5 7	5 2	7 1	6 3	5 6	5 2	6 8	6 1	5 6	5 1	4 9					
				1 . 2 5	8 1	7 2	6 5	6 0	8 0	7 1	6 5	5 9	7 7	6 9	6 4	5 9	7 4	6 8	6 3	5 9	5 6					
下方投影面積		c m ²	1 . 5	8 5	7 7	7 0	6 5	8 4	7 6	7 0	6 5	8 1	7 4	6 9	6 4	7 8	7 2	6 8	6 4	6 1						
等価発光面積			c m ²	2 . 0	9 1	8 4	7 8	7 3	8 9	8 3	7 7	7 3	8 6	8 1	7 6	7 2	8 3	7 9	7 5	7 1	6 9					
取付高さ	器具間隔最大限			2 . 5	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 8	9 0	8 5	8 1	7 7	8 7	8 3	8 0	7 6	7 4					
H m		1 . 2 3 H m	縦方向 (B)	3 . 0	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 2	9 2	8 8	8 4	8 1	8 9	8 6	8 3	8 0	7 8					
H m		1 . 2 3 H m		4 . 0	9 9	9 5	9 2	8 8	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 6	9 2	9 0	8 7	8 5	8 3					
				5 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 6					
				7 . 0	1 0 3	1 0 1	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	8 9					
				1 0 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2					

