

屋内照明器具特性	
品番 (品名)	XND5 5 6 7 S V
光源	LED3500_80_5230 ×1 5230.0 lm
管理番号	K0179660 (0) DB 1
B Z 分類	BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		0 %	1 0 0 %	室指数	照明率 (X 0 . 0 1)																				Z C M
下方光束																									
保守率		良 中 否	0 . 7 6	0 . 6	8 0	7 2	6 8	6 5	7 9	7 2	6 8	6 5	7 7	7 1	6 7	6 5	7 6	7 1	6 7	6 4	6 3				
			0 . 7 2	0 . 8	8 7	8 1	7 7	7 4	8 6	8 1	7 7	7 4	8 5	8 0	7 6	7 4	8 3	7 9	7 6	7 3	7 2				
			0 . 6 4	1 . 0	9 2	8 6	8 3	8 0	9 1	8 6	8 2	8 0	8 9	8 5	8 2	7 9	8 7	8 4	8 1	7 9	7 7				
				1 . 2 5	9 5	9 1	8 7	8 5	9 4	9 0	8 7	8 4	9 3	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 2				
下方投影面積		c m ²	1 . 5	9 8	9 3	9 0	8 8	9 7	9 3	9 0	8 7	9 5	9 1	8 9	8 7	9 3	9 0	8 8	8 6	8 5					
等価発光面積			c m ²	2 . 0	1 0 0	9 7	9 4	9 2	9 9	9 6	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 2	9 0	8 8				
取付高さ	器具間隔最大限			2 . 5	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 4	9 2	9 0				
横方向 (A)		縦方向 (B)		3 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 7	9 5	9 8	9 7	9 5	9 4	9 2				
H m	1 . 0 6 H m	1 . 0 6 H m	4 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 7	9 9	9 8	9 7	9 6	9 4					
			5 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5					
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 1 0	1 1 0	1 1 0	1 0 0	9 9	9 6				
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 7					

