

屋内照明器具特性	
品番 (品名)	XND7597SV
光源	LED3500_80_7975 ×1 7975.0 lm
管理番号	K0179649 (0) DB 1
BZ分類	BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束				1 0 0 %																		
保守率		良 中 否	0 . 7 6	0 . 6	7 1	6 3	5 7	5 3	7 0	6 2	5 7	5 3	6 9	6 1	5 6	5 3	6 7	6 1	5 6	5 3	5 1	
			0 . 7 2	0 . 8	8 1	7 3	6 8	6 4	8 0	7 2	6 7	6 4	7 8	7 1	6 7	6 3	7 6	7 0	6 6	6 3	6 2	
			0 . 6 4	1 . 0	8 6	8 0	7 5	7 1	8 5	7 9	7 4	7 1	8 3	7 8	7 4	7 0	8 1	7 7	7 3	7 0	6 8	
				1 . 2 5	9 1	8 5	8 1	7 7	9 0	8 4	8 0	7 7	8 8	8 3	7 9	7 6	8 6	8 2	7 8	7 6	7 4	
下方投影面積		c m ²	1 . 5	9 4	8 9	8 5	8 1	9 3	8 8	8 4	8 1	9 1	8 6	8 3	8 0	8 9	8 5	8 2	8 0	7 8		
等価発光面積			c m ²	2 . 0	9 8	9 3	9 0	8 7	9 7	9 3	8 9	8 7	9 4	9 1	8 8	8 6	9 2	8 9	8 7	8 5	8 3	
取付高さ	器具間隔最大限			2 . 5	1 0 0	9 6	9 3	9 1	9 9	9 5	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 6	
横方向 (A)		縦方向 (B)		3 . 0	1 0 1	9 8	9 6	9 3	1 0 0	9 7	9 5	9 3	9 8	9 6	9 3	9 2	9 6	9 4	9 2	9 1	8 8	
H m	1 . 1 5 H m	1 . 1 5 H m	4 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 6	9 5	9 3	9 1		
			5 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3		
			7 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5		
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 9	9 6		

