

屋内照明器具特性	
品番 (品名)	XND3537WL
光源	LED3000_80_3640 ×1 3640.0 lm
管理番号	K0179592 (1) DB 1
BZ分類	BZ1 / 3.5 / BZ2 / 8.5 / BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		0 %	1 0 0 %	室指数	照明率 (X 0 . 0 1)																				Z C M
下方光束																									
保守率		良 中 否	0 . 7 6	0 . 6	7 5	6 7	6 1	5 8	7 4	6 6	6 1	5 8	7 2	6 5	6 1	5 8	7 1	6 5	6 0	5 7	5 6				
			0 . 7 2	0 . 8	8 3	7 5	7 0	6 7	8 2	7 5	7 0	6 7	8 0	7 4	6 9	6 6	7 8	7 3	6 9	6 6	6 5				
			0 . 6 4	1 . 0	8 8	8 1	7 6	7 3	8 6	8 0	7 6	7 2	8 4	7 9	7 5	7 2	8 3	7 8	7 5	7 2	7 0				
				1 . 2 5	9 2	8 6	8 1	7 8	9 0	8 5	8 1	7 8	8 8	8 4	8 0	7 7	8 6	8 2	7 9	7 7	7 5				
下方投影面積		c m ²		1 . 5	9 4	8 9	8 5	8 2	9 3	8 8	8 4	8 1	9 1	8 7	8 3	8 1	8 9	8 5	8 2	8 0	7 8				
等価発光面積		c m ²		2 . 0	9 8	9 3	9 0	8 7	9 6	9 3	8 9	8 7	9 4	9 1	8 8	8 6	9 2	8 9	8 7	8 5	8 3				
取付 高さ	器具間隔最大限			2 . 5	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	9 0	9 6	9 3	9 1	8 9	9 4	9 2	9 0	8 8	8 6				
	横方向 (A)		縦方向 (B)	3 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 2	9 8	9 5	9 3	9 1	9 6	9 4	9 2	9 0	8 8				
H m	1 . 2 0 H m		1 . 2 0 H m	4 . 0	1 0 3	1 0 1	9 8	9 6	1 0 2	1 0 0	9 7	9 6	9 9	9 8	9 6	9 4	9 7	9 6	9 4	9 3	9 1				
				5 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2				
				7 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4				
				1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6				

