

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD3020LCE1 x2 795.0 1m
管理番号	K0194489 (2) D 1
BZ分類	BZ1

器具効率	58 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	29 %	反射率	壁	10 %				10 %				10 %				10 %				0 %
下方光束	29 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.9	3.5	3.3	3.1	3.7	3.4	3.2	3.0	3.4	3.1	3.0	2.8	3.0	2.9	2.8	2.7	2.4
	中	0.6	0.8	4.3	3.9	3.6	3.4	4.0	3.7	3.5	3.3	3.6	3.4	3.2	3.1	3.2	3.1	3.0	2.9	2.5
	否	0.56	1.0	4.5	4.1	3.9	3.7	4.2	3.9	3.7	3.6	3.8	3.6	3.4	3.3	3.3	3.2	3.1	3.0	2.6
下方投影面積	cm ²	1.25	4.7	4.4	4.1	3.9	4.4	4.1	3.9	3.8	3.9	3.7	3.6	3.5	3.4	3.3	3.2	3.1	2.7	
		1.5	4.8	4.5	4.3	4.1	4.5	4.3	4.1	4.0	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	2.7	
等価発光面積	cm ²	2.0	5.0	4.8	4.6	4.4	4.7	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.6	3.5	3.4	3.4	2.8	
		2.5	5.1	4.9	4.7	4.6	4.8	4.6	4.5	4.4	4.2	4.1	4.0	3.9	3.6	3.6	3.5	3.4	2.8	
取付高さ	器具間隔最大限		3.0	5.2	5.0	4.9	4.7	4.9	4.7	4.6	4.5	4.3	4.2	4.1	4.0	3.7	3.6	3.6	3.5	2.8
	横方向 (A)	縦方向 (B)	4.0	5.3	5.2	5.0	4.9	5.0	4.9	4.7	4.7	4.3	4.2	4.2	4.1	3.7	3.7	3.6	3.6	2.8
Hm	0.40Hm	0.39Hm	5.0	5.4	5.3	5.1	5.1	5.0	4.9	4.8	4.8	4.4	4.3	4.2	4.2	3.7	3.7	3.7	3.6	2.8
			7.0	5.4	5.4	5.3	5.2	5.1	5.0	5.0	4.9	4.4	4.4	4.3	4.3	3.8	3.8	3.7	3.7	2.9
			10.0	5.5	5.4	5.4	5.3	5.1	5.1	5.0	5.0	4.5	4.4	4.4	4.4	3.8	3.8	3.8	3.8	2.9

