

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD4000LCE1 x2 845.0 lm
管理番号	K0194440(2)D 1
BZ分類	BZ1

器具効率	14%	天井	80%				70%				50%				30%				0%
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	7%	床	10%				10%				10%				10%				0%
下方光束	7%	室指数	照明率 (X0.01) ZCM																
保守率	良	0.63	0.6	9	7	7	6	8	7	6	6	7	6	6	6	6	5	5	4
	中	0.6	0.8	10	9	8	7	9	8	7	7	8	7	7	6	7	7	6	5
	否	0.56	1.0	10	9	9	8	10	9	8	8	9	8	7	7	7	7	6	5
			1.25	11	10	9	9	10	10	9	8	9	8	8	8	8	7	7	6
下方投影面積		cm ²	1.5	11	11	10	9	11	10	9	9	9	9	8	8	8	8	7	6
等価発光面積		cm ²	2.0	12	11	11	10	11	11	10	10	10	9	9	9	8	8	8	6
取付高さ	器具間隔最大限		2.5	12	12	11	11	12	11	11	10	10	10	9	9	9	8	8	6
	横方向 (A)	縦方向 (B)	3.0	13	12	12	11	12	11	11	11	10	10	10	9	9	8	8	6
Hm	0.72Hm	0.72Hm	4.0	13	12	12	12	12	12	11	11	10	10	10	10	9	9	8	6
			5.0	13	13	12	12	12	12	12	11	10	10	10	9	9	9	9	7
			7.0	13	13	13	13	12	12	12	12	11	10	10	10	9	9	9	7
			10.0	13	13	13	13	12	12	12	12	11	11	11	10	9	9	9	7

