

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD20001CQ1 x2 531.0 lm
管理番号	K0194447(1)D 1
BZ分類	BZ1

器具効率	16%	天井	80%				70%				50%				30%				0%											
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%											
上方光束	8%	床	10%				10%				10%				10%				0%											
下方光束	8%	室指数	照明率 (X0.01) ZCM																											
保守率	良	0.63	0.6	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	10	8	7	9	8	7	7	8	7	7	6	7	7	6	6	5	
	中	0.6	0.8	1.1	1.2	1.3	1.4	1.4	1.4	1.4	1.4	1.5	1.5	11	10	9	10	9	8	8	9	8	8	7	8	7	7	7	6	
	否	0.56	1.0	1.2	1.3	1.4	1.4	1.4	1.4	1.4	1.5	1.5	12	10	9	11	10	9	9	10	9	9	8	8	8	7	7	6		
			0.56	1.25	1.2	1.3	1.4	1.4	1.4	1.4	1.5	1.5	10	10	9	11	11	10	10	10	10	9	9	8	8	8	7	7	6	
下方投影面積	cm ²		1.5	1.2	1.1	1.1	1.2	1.1	1.1	1.0	1.0	1.0	1.0	10	10	9	10	10	10	10	10	9	9	9	9	8	8	7		
等価発光面積	cm ²		2.0	1.3	1.2	1.1	1.2	1.2	1.1	1.1	1.1	1.0	1.0	10	10	10	10	10	10	10	10	9	9	9	9	9	8	8	7	
取付高さ	器具間隔最大限		2.5	1.4	1.3	1.2	1.2	1.3	1.2	1.2	1.1	1.1	1.1	10	10	10	10	10	10	10	10	9	9	9	9	9	9	9	7	
	横方向 (A)	縦方向 (B)	3.0	1.4	1.3	1.3	1.2	1.3	1.3	1.2	1.2	1.1	1.1	10	10	10	10	10	10	10	10	9	9	9	9	9	9	9	7	
Hm	0.74Hm	0.74Hm	4.0	1.4	1.4	1.3	1.3	1.3	1.3	1.2	1.2	1.1	1.1	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	9	7
			5.0	1.4	1.4	1.4	1.3	1.3	1.3	1.3	1.2	1.1	1.1	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	7
			7.0	1.5	1.4	1.4	1.4	1.4	1.3	1.3	1.2	1.2	1.2	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	7
			10.0	1.5	1.5	1.4	1.4	1.4	1.4	1.3	1.2	1.2	1.2	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	8

