

| | |
|----------|--|
| 屋内照明器具特性 | |
| 品番 (品名) | YYY41000 |
| 光源 | LLD40402CQ1 (KAKUSAN) ×2 860.0 1m |
| 管理番号 | K0194448 (1) D 1 |
| BZ分類 | BZ1 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|---|
| 器具効率 | 12% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 6% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 6% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.63 | 0.6 | 7 | 6 | 5 | 5 | 6 | 6 | 5 | 5 | 6 | 5 | 5 | 4 | 5 | 5 | 4 | 4 | 3 |
| | 中 | 0.6 | 0.8 | 8 | 7 | 6 | 6 | 7 | 6 | 6 | 6 | 6 | 6 | 5 | 5 | 6 | 5 | 5 | 5 | 4 |
| | 否 | 0.56 | 1.0 | 8 | 8 | 7 | 6 | 8 | 7 | 7 | 6 | 7 | 6 | 6 | 6 | 6 | 6 | 5 | 5 | 4 |
| | | | 1.25 | 9 | 8 | 8 | 7 | 8 | 8 | 7 | 7 | 7 | 7 | 6 | 6 | 6 | 6 | 6 | 5 | 4 |
| 下方投影面積 | | cm ² | 1.5 | 9 | 9 | 8 | 8 | 9 | 8 | 8 | 7 | 7 | 7 | 7 | 6 | 6 | 6 | 6 | 5 | 4 |
| 等価発光面積 | | cm ² | 2.0 | 10 | 9 | 9 | 8 | 9 | 9 | 8 | 8 | 8 | 7 | 7 | 7 | 7 | 6 | 6 | 5 | 4 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 10 | 9 | 9 | 9 | 9 | 9 | 9 | 8 | 8 | 8 | 7 | 7 | 7 | 7 | 6 | 5 | 4 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 10 | 10 | 9 | 9 | 9 | 9 | 9 | 9 | 8 | 8 | 8 | 7 | 7 | 7 | 7 | 6 | 5 |
| Hm | 0.55Hm | 0.55Hm | 4.0 | 10 | 10 | 10 | 10 | 10 | 9 | 9 | 9 | 8 | 8 | 8 | 8 | 7 | 7 | 7 | 5 | 4 |
| | | | 5.0 | 11 | 10 | 10 | 10 | 10 | 10 | 9 | 9 | 8 | 8 | 8 | 8 | 7 | 7 | 7 | 5 | 4 |
| | | | 7.0 | 11 | 11 | 10 | 10 | 10 | 10 | 10 | 9 | 9 | 8 | 8 | 8 | 7 | 7 | 7 | 5 | 4 |
| | | | 10.0 | 11 | 11 | 11 | 10 | 10 | 10 | 10 | 10 | 9 | 9 | 9 | 8 | 7 | 7 | 7 | 5 | 4 |

