

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD40402CQ1 (SHUKOU) ×2 620.0 1 m
管理番号	K0194449 (1) D 1
BZ分類	BZ1

器具効率	58%	天井	80%				70%				50%				30%				0%		
	上方光束		29%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		29%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	3.8	3.3	3.0	2.8	3.6	3.2	2.9	2.7	3.2	2.9	2.7	2.6	2.8	2.6	2.5	2.4	2.2	
	中	0.6	0.8	4.1	3.7	3.4	3.2	3.9	3.5	3.3	3.1	3.5	3.2	3.0	2.9	3.1	2.9	2.8	2.7	2.3	
	否	0.56	1.0	4.4	4.0	3.7	3.5	4.1	3.8	3.6	3.4	3.7	3.4	3.3	3.1	3.2	3.1	2.9	2.9	2.4	
	下方投影面積	c m ²		1.25	4.6	4.3	4.0	3.8	4.3	4.0	3.8	3.6	3.8	3.6	3.5	3.3	3.3	3.2	3.1	3.0	2.5
等価発光面積	c m ²		1.5	4.8	4.5	4.2	4.0	4.5	4.2	4.0	3.8	3.9	3.7	3.6	3.5	3.4	3.3	3.2	3.1	2.6	
	c m ²		2.0	5.0	4.7	4.5	4.3	4.7	4.4	4.3	4.1	4.1	3.9	3.8	3.7	3.5	3.4	3.3	3.3	2.7	
取付高さ	器具間隔最大限		2.5	5.1	4.9	4.7	4.5	4.8	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.6	3.5	3.4	3.4	2.7	
	横方向 (A)	縦方向 (B)	3.0	5.2	5.0	4.8	4.7	4.9	4.7	4.6	4.4	4.2	4.1	4.0	3.9	3.6	3.6	3.5	3.4	2.7	
H m	0.70 H m	0.69 H m	4.0	5.3	5.1	5.0	4.9	5.0	4.8	4.7	4.6	4.3	4.2	4.1	4.1	3.7	3.6	3.6	3.5	2.8	
			5.0	5.4	5.2	5.1	5.0	5.0	4.9	4.8	4.7	4.3	4.3	4.2	4.2	3.7	3.7	3.6	3.6	2.8	
			7.0	5.4	5.3	5.3	5.2	5.1	5.0	4.9	4.9	4.4	4.4	4.3	4.3	3.8	3.7	3.7	3.7	2.8	
			10.0	5.5	5.4	5.4	5.3	5.1	5.1	5.0	5.0	4.4	4.4	4.4	4.3	3.8	3.8	3.7	3.7	2.8	

