

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD3000CU1 x2 795.0 lm
管理番号	K0194450(1)D 1
BZ分類	BZ1

器具効率	16%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	8%	床	10%				10%				10%				10%				0%	
下方光束	8%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	9	8	7	6	9	7	7	6	8	7	6	6	7	6	6	5	5
	中	0.6	0.8	10	9	8	8	10	9	8	7	9	8	7	7	7	7	6	6	5
	否	0.56	1.0	11	10	9	9	11	10	9	8	9	8	8	7	8	7	7	7	6
			1.25	12	11	10	9	11	10	10	9	10	9	9	8	8	8	8	7	6
下方投影面積		cm ²	1.5	12	11	11	10	12	11	10	10	10	9	9	9	9	8	8	8	6
等価発光面積		cm ²	2.0	13	12	12	11	12	11	11	10	10	10	9	9	9	8	8	8	6
取付高さ	器具間隔最大限		2.5	13	13	12	12	12	12	11	11	11	10	10	10	9	9	9	8	7
	横方向 (A)	縦方向 (B)	3.0	14	13	13	12	13	12	12	11	11	11	10	10	9	9	9	9	7
H _m	0.75H _m	0.74H _m	4.0	14	14	13	13	13	13	12	12	11	11	11	10	9	9	9	7	
			5.0	14	14	13	13	13	13	13	12	11	11	11	11	10	9	9	7	
			7.0	14	14	14	14	13	13	13	13	12	11	11	11	10	10	10	7	
			10.0	15	14	14	14	14	13	13	13	12	12	11	11	10	10	10	7	

