

# 屋内照明器具特性

品番 (品名)	YYY41000	
光源	LLD3020CU1 ×2	615.0 lm
管理番号	K0194452(1)D 1	
BZ分類	BZ1	

器具効率	57%	天井	80%				70%				50%				30%				0%					
	上方光束		28%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
下方光束	29%	床	10%				10%				10%				10%				0%					
室指数	照明率 (X0.01)																ZCM							
保守率	良	0.63	0.6	0.56	0.6	40	36	33	31	38	34	32	31	34	32	30	29	31	29	28	27	25		
	中	0.6	0.6	0.56	0.8	43	39	37	35	41	37	35	34	36	34	33	31	32	31	30	29	26		
	否	0.56	1.0	45	42	39	37	42	40	37	36	38	36	34	33	33	32	31	31	31	27	27		
下方投影面積	等価発光面積	cm <sup>2</sup>	cm <sup>2</sup>	1.25	47	44	41	40	44	42	40	38	39	37	36	35	34	33	32	32	27	27		
				1.5	48	45	43	41	45	43	41	40	40	38	37	36	35	34	33	33	33	27	27	
取付高さ	器具間隔最大限		Hm	0.32Hm	Hm	0.32Hm	2.5	51	49	48	46	48	46	45	44	42	41	40	39	36	36	35	35	28
	横方向 (A)	縦方向 (B)					3.0	52	50	49	47	49	47	46	45	43	42	41	40	37	36	36	35	28
Hm	0.32Hm	0.32Hm	4.0	53	52	50	49	50	48	47	47	43	42	42	41	37	37	36	36	29	29			
			5.0	54	52	51	51	50	49	48	48	44	43	42	42	37	37	37	37	29	29			
Hm	0.32Hm	0.32Hm	7.0	54	53	53	52	51	50	49	49	44	44	43	43	38	38	37	37	29	29			
			10.0	55	54	54	53	51	51	50	50	44	44	44	44	38	38	38	38	29	29			

