

屋内照明器具特性

品番 (品名)	YYY41000+YYY90250+YYY902															
光源	LLD3020LCE1 x2 795.0 lm															
管理番号	K0194462(1)D1															
BZ分類	BZ1															

器具効率	16%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	8%	反射率	10%				10%				10%				10%				0%	
下方光束	8%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	11	10	9	9	11	10	9	9	10	9	9	8	9	8	8	8	7
	中	0.6	0.8	12	11	10	10	11	10	10	9	10	10	9	9	9	9	8	8	7
	否	0.56	1.0	12	12	11	10	12	11	10	10	10	10	9	9	9	9	9	9	7
			1.25	13	12	12	11	12	12	11	11	11	10	10	10	9	9	9	9	7
下方投影面積			1.5	13	13	12	12	13	12	11	11	11	11	10	10	10	9	9	9	8
等価発光面積			2.0	14	13	13	12	13	12	12	12	11	11	11	10	10	10	9	9	8
取付高さ	器具間隔最大限		2.5	14	14	13	13	13	13	12	12	12	11	11	11	10	10	10	9	8
	横方向 (A)	縦方向 (B)	3.0	14	14	13	13	13	13	12	12	11	11	11	10	10	10	10	10	8
Hm	0.37Hm	0.37Hm	4.0	15	14	14	14	14	13	13	13	12	12	11	11	10	10	10	10	8
			5.0	15	14	14	14	14	14	13	13	12	12	12	12	10	10	10	10	8
			7.0	15	15	15	14	14	14	14	13	12	12	12	12	10	10	10	10	8
			10.0	15	15	15	15	14	14	14	14	12	12	12	12	10	10	10	10	8

