

屋内照明器具特性	
品番 (品名)	XND2006SBZ
光源	LED4000_85_1600 x1 1600.0 lm
管理番号	K0176481 (0) DB 1
BZ分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		1 0 0 %																					
保守率		良	0 . 6	7 9	7 2	6 7	6 4	7 8	7 2	6 7	6 4	7 7	7 1	6 7	6 4	7 5	7 0	6 7	6 4	6 3			
		中	0 . 8	8 7	8 1	7 6	7 3	8 6	8 0	7 6	7 3	8 4	7 9	7 5	7 3	8 3	7 8	7 5	7 3	7 1			
		否	0 . 7 7	1 . 0	9 1	8 6	8 2	7 9	9 0	8 5	8 1	7 9	8 9	8 4	8 1	7 8	8 7	8 3	8 0	7 8	7 6		
			0 . 6 8	1 . 2 5	9 5	9 0	8 7	8 4	9 4	8 9	8 6	8 3	9 2	8 8	8 5	8 3	9 0	8 7	8 5	8 2	8 1		
下方投影面積		c m ²	1 . 5	9 7	9 3	9 0	8 7	9 6	9 2	8 9	8 7	9 4	9 1	8 8	8 6	9 2	9 0	8 7	8 6	8 4			
等価発光面積			c m ²	2 . 0	1 0 0	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	9 0	8 8		
取付	器具間隔最大限		2 . 5	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	9 0			
高さ	横方向 (A)		縦方向 (B)	3 . 0	1 0 3	1 0 1	9 8	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 6	9 5	9 4	9 2		
H m	0 . 7 4 H m		0 . 7 4 H m	4 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 4		
				5 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5		
				7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6		
				1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 7		

