

屋内照明器具特性	
品番 (品名)	X N W5 5 6 0 W L
光源	L E D 3 0 0 0 _ 8 0 _ 4 3 9 0 x 1 4 3 9 0 . 0 l m
管理番号	K 0 1 7 2 5 3 2 (0) D B 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %	室指数	床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		1 0 0 %		照明率 (X 0 . 0 1) Z C M																	
保守率		良	0 . 7 6	0 . 6	8 3	7 7	7 3	7 0	8 2	7 7	7 3	7 0	8 1	7 6	7 3	7 0	8 0	7 5	7 2	7 0	6 9
		中	0 . 7 2	0 . 8	8 9	8 4	8 0	7 8	8 9	8 3	8 0	7 7	8 7	8 3	7 9	7 7	8 6	8 2	7 9	7 7	7 6
		否	0 . 6 4	1 . 0	9 3	8 8	8 5	8 2	9 2	8 8	8 5	8 2	9 1	8 7	8 4	8 2	8 9	8 6	8 3	8 1	8 0
		下方投影面積 等価発光面積		c m ² c m ²	1 . 2 5	9 6	9 2	8 9	8 6	9 5	9 1	8 8	8 6	9 4	9 0	8 8	8 6	9 2	8 9	8 7	8 5
1 . 5	9 8				9 4	9 2	8 9	9 7	9 4	9 1	8 9	9 5	9 2	9 0	8 8	9 4	9 1	8 9	8 8	8 6	
2 . 0	1 0 1				9 8	9 5	9 3	1 0 0	9 7	9 5	9 3	9 8	9 5	9 3	9 2	9 6	9 4	9 2	9 1	8 9	
取付 高さ	器具間隔最大限		2 . 5	1 0 2	1 0 0	9 7	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 6	9 4	9 3	9 1	
	横方向 (A)	縦方向 (B)	3 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 6	9 8	9 7	9 6	9 5	9 2	
H m	0 . 7 6 H m	0 . 7 6 H m	4 . 0	1 0 4	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4	
			5 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5	
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 9	9 6	
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 7	

