

屋内照明器具特性

品番 (品名)	XNN2 5 5 6 WV	
光源	LED3500_85_2350 ×1	2350.0 lm
管理番号	K0176635 (0) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %
下方光束	100 %		壁	10 %				10 %				10 %				10 %			
		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)																ZCM
保守率	良 0.81	0.6	87	82	78	76	87	82	78	76	85	81	78	76	84	80	78	76	75
	中 0.77	0.8	93	88	85	82	92	88	85	82	91	87	84	82	89	86	84	82	81
	否 0.68	1.0	96	92	89	87	95	91	89	87	94	91	88	86	92	90	87	86	85
下方投影面積	cm ²	1.25	99	95	92	90	98	95	92	90	96	93	91	89	95	92	90	89	88
		1.5	100	97	95	93	99	97	94	92	98	95	93	92	96	94	92	91	90
等価発光面積	cm ²	2.0	102	100	98	96	102	99	97	95	100	98	96	95	98	96	95	94	92
		2.5	104	102	100	98	103	101	99	98	101	99	98	96	99	98	97	95	94
取付高さ	器具間隔最大限		3.0	105	103	101	100	104	102	100	99	102	100	99	98	100	99	98	95
	横方向 (A)	縦方向 (B)	4.0	106	104	103	102	105	103	102	101	103	101	100	99	101	100	99	98
Hm	0.77Hm	0.77Hm	5.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	
			7.0	107	106	105	104	106	105	104	104	103	102	102	101	101	100	99	
			10.0	107	107	106	106	106	105	105	104	104	103	103	102	102	101	101	

