

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XND2507WCZ                  |
| 光源       | LED3500_85_1865 ×1 1865.0lm |
| 管理番号     | K0176490 ( 0 ) DB 1         |
| BZ分類     | BZ1                         |

| 器具効率         |                 | 100 %           | 反射率             | 天井                | 80 % |     |     |     |     | 70 % |     |     |     |     | 50 % |     |     |    |    | 30 % |     |  |  |  | 0 % |
|--------------|-----------------|-----------------|-----------------|-------------------|------|-----|-----|-----|-----|------|-----|-----|-----|-----|------|-----|-----|----|----|------|-----|--|--|--|-----|
|              |                 |                 |                 | 壁                 | 70   | 50  | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30   | 10  | 70  | 50 | 30 | 10   | 0 % |  |  |  |     |
|              |                 |                 |                 | 床                 | 10 % |     |     |     |     | 10 % |     |     |     |     | 10 % |     |     |    |    | 10 % |     |  |  |  | 0 % |
| 上方光束<br>下方光束 |                 | 100 %           | 室指数             | 照明率 ( X0.01 ) ZCM |      |     |     |     |     |      |     |     |     |     |      |     |     |    |    |      |     |  |  |  |     |
| 保守率          |                 | 良<br>中<br>否     | 0.81            | 0.6               | 73   | 64  | 58  | 55  | 72  | 64   | 58  | 55  | 70  | 63  | 58   | 54  | 68  | 62 | 57 | 54   | 53  |  |  |  |     |
|              |                 |                 | 0.77            | 0.8               | 82   | 74  | 69  | 65  | 81  | 74   | 69  | 65  | 79  | 73  | 68   | 65  | 77  | 72 | 68 | 65   | 63  |  |  |  |     |
|              |                 |                 | 0.68            | 1.0               | 87   | 81  | 76  | 72  | 86  | 80   | 76  | 72  | 84  | 79  | 75   | 72  | 82  | 78 | 74 | 71   | 70  |  |  |  |     |
|              |                 |                 |                 | 1.25              | 92   | 86  | 82  | 78  | 91  | 85   | 81  | 78  | 88  | 84  | 80   | 77  | 86  | 83 | 79 | 77   | 75  |  |  |  |     |
| 下方投影面積       |                 | cm <sup>2</sup> | 1.5             | 94                | 89   | 85  | 82  | 93  | 89  | 85   | 82  | 91  | 87  | 84  | 81   | 89  | 86  | 83 | 81 | 79   |     |  |  |  |     |
| 等価発光面積       |                 |                 | cm <sup>2</sup> | 2.0               | 98   | 94  | 90  | 88  | 97  | 93   | 90  | 87  | 95  | 91  | 89   | 86  | 93  | 90 | 88 | 86   | 84  |  |  |  |     |
| 取付<br>高さ     | 器具間隔最大限         |                 | 2.5             | 100               | 97   | 94  | 91  | 99  | 96  | 93   | 91  | 97  | 94  | 92  | 90   | 95  | 92  | 90 | 89 | 87   |     |  |  |  |     |
|              | 横方向 (A) 縦方向 (B) |                 | 3.0             | 102               | 99   | 96  | 94  | 100 | 98  | 95   | 93  | 98  | 96  | 94  | 92   | 96  | 94  | 92 | 91 | 89   |     |  |  |  |     |
| H m          | 1.17 H m        | 1.17 H m        | 4.0             | 103               | 101  | 99  | 97  | 102 | 100 | 98   | 96  | 100 | 98  | 96  | 95   | 98  | 96  | 95 | 94 | 91   |     |  |  |  |     |
|              |                 |                 | 5.0             | 104               | 102  | 101 | 99  | 103 | 101 | 100  | 98  | 101 | 99  | 98  | 97   | 99  | 98  | 96 | 95 | 93   |     |  |  |  |     |
|              |                 |                 | 7.0             | 106               | 104  | 103 | 102 | 104 | 103 | 102  | 101 | 102 | 101 | 100 | 99   | 100 | 99  | 98 | 97 | 95   |     |  |  |  |     |
|              |                 |                 | 10.0            | 106               | 105  | 104 | 104 | 105 | 104 | 103  | 103 | 103 | 102 | 101 | 101  | 100 | 100 | 99 | 99 | 96   |     |  |  |  |     |

