

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | YYY41000                |
| 光源       | LLD4000LCE1 ×2 845.0 lm |
| 管理番号     | K0194440 (2) D 1        |
| BZ分類     | BZ1                     |

| 器具効率   |  | 14 %<br><br>上方光束<br>7 %<br>下方光束<br>7 % | 反射率             | 天井                  | 80 %               |     |     |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|--|----------------------------------------|-----------------|---------------------|--------------------|-----|-----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|        |  |                                        |                 | 壁                   | 70                 | 50  | 30  | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |  |                                        |                 | 床                   | 10 %               |     |     |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |  |                                        |                 | 室指数                 | 照明率 ( X0.01 ) Z CM |     |     |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率    |  | 良<br>中<br>否                            | 0.63            | 0.6                 | 9                  | 7   | 7   | 6  | 8    | 7  | 6  | 6  | 7    | 6  | 6  | 6  | 6    | 5  | 5  | 4  |     |
|        |  |                                        | 0.6             | 0.8                 | 10                 | 9   | 8   | 7  | 9    | 8  | 7  | 7  | 8    | 7  | 7  | 6  | 7    | 7  | 6  | 6  | 5   |
|        |  |                                        | 0.56            | 1.0                 | 10                 | 9   | 9   | 8  | 10   | 9  | 8  | 8  | 9    | 8  | 7  | 7  | 7    | 7  | 7  | 6  | 5   |
|        |  |                                        | 1.25            | 1.1                 | 10                 | 9   | 9   | 10 | 10   | 9  | 8  | 9  | 8    | 8  | 8  | 8  | 7    | 7  | 7  | 6  |     |
| 下方投影面積 |  | cm <sup>2</sup>                        | 1.5             | 1.1                 | 11                 | 10  | 9   | 11 | 10   | 9  | 9  | 9  | 9    | 8  | 8  | 8  | 8    | 7  | 7  | 6  |     |
| 等価発光面積 |  |                                        | cm <sup>2</sup> | 2.0                 | 1.2                | 11  | 11  | 10 | 11   | 11 | 10 | 10 | 10   | 9  | 9  | 9  | 8    | 8  | 8  | 6  |     |
| 取付高さ   |  |                                        |                 | 器具間隔最大限             |                    | 2.5 | 1.2 | 12 | 11   | 11 | 12 | 11 | 11   | 10 | 10 | 10 | 9    | 9  | 9  | 8  | 6   |
|        |  |                                        |                 | 横方向 ( A ) 縦方向 ( B ) |                    | 3.0 | 1.3 | 12 | 12   | 11 | 12 | 11 | 11   | 11 | 10 | 10 | 10   | 9  | 9  | 8  | 8   |
| H m    |  | 0.72 H m                               |                 | 0.72 H m            | 4.0                | 1.3 | 12  | 12 | 12   | 12 | 12 | 11 | 11   | 10 | 10 | 10 | 10   | 9  | 9  | 8  | 6   |
|        |  |                                        |                 | 5.0                 | 1.3                | 13  | 12  | 12 | 12   | 12 | 12 | 11 | 10   | 10 | 10 | 10 | 9    | 9  | 9  | 7  |     |
|        |  |                                        |                 | 7.0                 | 1.3                | 13  | 13  | 13 | 12   | 12 | 12 | 12 | 11   | 10 | 10 | 10 | 9    | 9  | 9  | 7  |     |
|        |  |                                        |                 | 10.0                | 1.3                | 13  | 13  | 13 | 12   | 12 | 12 | 12 | 11   | 11 | 11 | 10 | 9    | 9  | 9  | 7  |     |

