

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD40402CQ1 (SHUKOU) ×2 620.0 l m
管理番号	K0194449 (1) D 1
BZ分類	BZ1

器具効率		58 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01)																Z C M	
保守率		良 中 否	0.63	0.6	38	33	30	28	36	32	29	27	32	29	27	26	28	26	25	24	22	
			0.6	0.8	41	37	34	32	39	35	33	31	35	32	30	29	31	29	28	27	23	
				1.0	44	40	37	35	41	38	36	34	37	34	33	31	32	31	29	29	24	
			0.56	1.25	46	43	40	38	43	40	38	36	38	36	35	33	33	32	31	30	25	
下方投影面積		cm ²		1.5	48	45	42	40	45	42	40	38	39	37	36	35	34	33	32	31	26	
			等価発光面積		cm ²	2.0	50	47	45	43	47	44	43	41	41	39	38	37	35	34	33	33
取付 高さ	器具間隔最大限					2.5	51	49	47	45	48	46	44	43	42	40	39	38	36	35	34	34
		横方向 (A)		縦方向 (B)		3.0	52	50	48	47	49	47	46	44	42	41	40	39	36	36	35	34
H m	0.70 H m		0.69 H m		4.0	53	51	50	49	50	48	47	46	43	42	41	41	37	36	36	35	28
					5.0	54	52	51	50	50	49	48	47	43	43	42	42	37	37	36	36	28
					7.0	54	53	53	52	51	50	49	49	44	44	43	43	38	37	37	37	28
					10.0	55	54	54	53	51	51	50	50	44	44	44	43	38	38	37	37	28

