

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD4000LCT1 ×2 845.0 lm
管理番号	K0194454 (1) D 1
BZ分類	BZ1

器具効率	15 % 上方光束 7 % 下方光束 8 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		壁	10 %				10 %				10 %				10 %				0 %
		床	照明率 (X0.01)				Z CM												
保守率	良 0.63	0.6	9	8	7	6	8	7	7	6	7	7	6	6	7	6	6	5	5
	中 0.6	0.8	10	9	8	8	9	8	8	7	8	8	7	7	7	7	6	6	5
	否 0.56	1.0	11	10	9	8	10	9	9	8	9	8	8	7	8	7	7	7	6
		1.25	11	11	10	9	11	10	9	9	9	9	8	8	8	8	7	7	6
下方投影面積 等価発光面積	cm ²	1.5	12	11	10	10	11	10	10	9	10	9	9	8	8	8	8	7	6
	cm ²	2.0	12	12	11	11	12	11	11	10	10	10	9	9	9	8	8	8	6
		2.5	13	12	12	11	12	11	11	11	10	10	10	9	9	9	8	8	6
		3.0	13	13	12	12	12	12	11	11	11	10	10	10	9	9	9	8	7
取付高さ	器具間隔最大限		4.0	13	13	13	12	12	12	12	11	11	10	10	9	9	9	9	7
H m	0.71 H m	0.72 H m	5.0	14	13	13	13	13	12	12	11	11	11	10	9	9	9	9	7
			7.0	14	13	13	13	13	12	12	11	11	11	11	9	9	9	9	7
			10.0	14	14	14	13	13	13	13	11	11	11	11	9	9	9	9	7

