

屋内照明器具特性	
品番 (品名)	XS Z B 1 0 3 5 0
光源	LLD2401LCB1 ×1 500.0 l m
管理番号	K0193966 (0) DB 1
B Z 分類	B Z 1

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %		
下方光束	79 %	室指数	照明率 (X0.01)																Z C M		
保守率	良	0.67	0.6	5.7	5.0	4.5	4.2	5.6	4.9	4.5	4.2	5.5	4.9	4.5	4.2	5.3	4.8	4.5	4.2	4.1	
	中	0.63	0.8	6.4	5.8	5.4	5.1	6.3	5.8	5.4	5.1	6.2	5.7	5.4	5.1	6.0	5.6	5.3	5.1	5.0	
	否	0.56	1.0	6.9	6.4	6.0	5.7	6.8	6.3	6.0	5.7	6.6	6.2	5.9	5.7	6.5	6.1	5.8	5.6	5.5	
			1.25	7.2	6.8	6.4	6.2	7.1	6.7	6.4	6.2	7.0	6.6	6.3	6.1	6.8	6.5	6.3	6.1	6.0	
下方投影面積		cm ²	1.5	7.5	7.1	6.8	6.5	7.4	7.0	6.7	6.5	7.2	6.9	6.6	6.4	7.0	6.8	6.6	6.4	6.2	
等価発光面積		cm ²	2.0	7.7	7.4	7.2	6.9	7.7	7.4	7.1	6.9	7.5	7.2	7.0	6.8	7.3	7.1	6.9	6.8	6.6	
取付高さ	器具間隔最大限		2.5	7.9	7.6	7.4	7.2	7.8	7.6	7.4	7.2	7.6	7.4	7.3	7.1	7.5	7.3	7.2	7.0	6.9	
	横方向 (A)	縦方向 (B)	3.0	8.0	7.8	7.6	7.4	7.9	7.7	7.5	7.4	7.8	7.6	7.4	7.3	7.6	7.4	7.3	7.2	7.0	
H m	1.32 H m	1.32 H m	4.0	8.2	8.0	7.8	7.7	8.1	7.9	7.8	7.6	7.9	7.8	7.6	7.5	7.7	7.6	7.5	7.4	7.2	
			5.0	8.2	8.1	8.0	7.8	8.1	8.0	7.9	7.8	8.0	7.9	7.8	7.7	7.8	7.7	7.6	7.5	7.4	
			7.0	8.3	8.2	8.1	8.0	8.2	8.1	8.0	8.0	8.1	8.0	7.9	7.8	7.9	7.8	7.8	7.7	7.5	
			10.0	8.4	8.3	8.2	8.2	8.3	8.2	8.2	8.1	8.1	8.1	8.0	8.0	8.0	8.0	7.9	7.9	7.8	7.6

