

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XNS 1 0 6 0 WL K            |
| 光源       | LED3000_85_965 ×1 965.0 l m |
| 管理番号     | K0183312 ( 0 ) DB 1         |
| BZ分類     | BZ1                         |

| 器具効率             |                 | 100 %           | 反射率             | 天井   | 80 %              |     |     |     |     | 70 % |     |     |     |     | 50 % |     |     |     |    | 30 % |     |  |  |  | 0 % |
|------------------|-----------------|-----------------|-----------------|------|-------------------|-----|-----|-----|-----|------|-----|-----|-----|-----|------|-----|-----|-----|----|------|-----|--|--|--|-----|
|                  |                 |                 |                 | 壁    | 70                | 50  | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30   | 10  | 70  | 50  | 30 | 10   | 0 % |  |  |  |     |
|                  |                 |                 |                 | 床    | 10 %              |     |     |     |     | 10 % |     |     |     |     | 10 % |     |     |     |    | 10 % |     |  |  |  | 0 % |
|                  |                 |                 |                 | 室指数  | 照明率 ( X0.01 ) ZCM |     |     |     |     |      |     |     |     |     |      |     |     |     |    |      |     |  |  |  |     |
| 保守率              |                 | 良<br>中<br>否     | 0.81            | 0.6  | 72                | 63  | 57  | 53  | 71  | 63   | 57  | 53  | 69  | 62  | 57   | 53  | 67  | 61  | 56 | 53   | 52  |  |  |  |     |
|                  |                 |                 | 0.77            | 0.8  | 81                | 74  | 68  | 65  | 80  | 73   | 68  | 64  | 78  | 72  | 68   | 64  | 76  | 71  | 67 | 64   | 62  |  |  |  |     |
|                  |                 |                 | 0.68            | 1.0  | 87                | 80  | 76  | 72  | 86  | 80   | 75  | 72  | 84  | 79  | 74   | 71  | 82  | 77  | 74 | 71   | 69  |  |  |  |     |
|                  |                 |                 |                 | 1.25 | 92                | 86  | 81  | 78  | 90  | 85   | 81  | 78  | 88  | 84  | 80   | 77  | 86  | 82  | 79 | 77   | 75  |  |  |  |     |
| 下方投影面積<br>等価発光面積 |                 | cm <sup>2</sup> |                 | 1.5  | 94                | 89  | 85  | 82  | 93  | 89   | 85  | 82  | 91  | 87  | 84   | 81  | 89  | 86  | 83 | 81   | 79  |  |  |  |     |
|                  |                 |                 | cm <sup>2</sup> | 2.0  | 98                | 94  | 91  | 88  | 97  | 93   | 90  | 87  | 95  | 91  | 89   | 86  | 93  | 90  | 88 | 86   | 84  |  |  |  |     |
| 取付<br>高さ         | 器具間隔最大限         |                 |                 | 2.5  | 100               | 97  | 94  | 91  | 99  | 96   | 93  | 91  | 97  | 94  | 92   | 90  | 95  | 92  | 91 | 89   | 87  |  |  |  |     |
|                  | 横方向 (A) 縦方向 (B) |                 |                 | 3.0  | 102               | 99  | 96  | 94  | 100 | 98   | 95  | 93  | 98  | 96  | 94   | 92  | 96  | 94  | 92 | 91   | 89  |  |  |  |     |
| H m              | 1.30 H m        | 1.30 H m        |                 | 4.0  | 103               | 101 | 99  | 97  | 102 | 100  | 98  | 96  | 100 | 98  | 97   | 95  | 98  | 96  | 95 | 94   | 91  |  |  |  |     |
|                  |                 |                 |                 | 5.0  | 104               | 102 | 101 | 99  | 103 | 101  | 100 | 98  | 101 | 99  | 98   | 97  | 99  | 98  | 97 | 95   | 93  |  |  |  |     |
|                  |                 |                 |                 | 7.0  | 106               | 104 | 103 | 102 | 104 | 103  | 102 | 101 | 102 | 101 | 100  | 99  | 100 | 99  | 98 | 97   | 95  |  |  |  |     |
|                  |                 |                 |                 | 10.0 | 106               | 105 | 104 | 104 | 105 | 104  | 103 | 103 | 103 | 102 | 101  | 101 | 100 | 100 | 99 | 99   | 96  |  |  |  |     |

