

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XNS 2 0 3 0 WAK              |
| 光源       | LED5000_85_1685 ×1 1685.0 lm |
| 管理番号     | K0183321 ( 0 ) DB 1          |
| B Z 分類   | BZ1                          |

| 器具効率      |          | 100 %           | 反射率             | 天井            | 80 % |     |     |     |     | 70 % |     |     |     |     | 50 % |     |     |     |    | 30 % |    |    |    |      | 0 % |
|-----------|----------|-----------------|-----------------|---------------|------|-----|-----|-----|-----|------|-----|-----|-----|-----|------|-----|-----|-----|----|------|----|----|----|------|-----|
|           |          |                 |                 | 壁             | 70   | 50  | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30   | 10  | 70  | 50  | 30 | 10   | 70 | 50 | 30 | 10   | 0 % |
|           |          |                 |                 | 床             | 10 % |     |     |     |     | 10 % |     |     |     |     | 10 % |     |     |     |    | 10 % |    |    |    |      | 0 % |
| 上方光束      |          | 0 %             | 室指数             | 照明率 ( X0.01 ) |      |     |     |     |     |      |     |     |     |     |      |     |     |     |    |      |    |    |    | Z CM |     |
| 下方光束      |          |                 |                 |               |      |     |     |     |     |      |     |     |     |     |      |     |     |     |    |      |    |    |    |      |     |
| 保守率       |          | 良<br>中<br>否     | 0.81            | 0.6           | 73   | 65  | 60  | 56  | 73  | 65   | 59  | 56  | 71  | 64  | 59   | 56  | 69  | 63  | 59 | 56   | 54 |    |    |      |     |
|           |          |                 | 0.77            | 0.8           | 82   | 75  | 70  | 66  | 81  | 75   | 70  | 66  | 80  | 74  | 69   | 66  | 78  | 73  | 69 | 66   | 64 |    |    |      |     |
|           |          |                 | 0.68            | 1.0           | 88   | 81  | 77  | 73  | 87  | 81   | 76  | 73  | 85  | 80  | 76   | 73  | 83  | 78  | 75 | 72   | 71 |    |    |      |     |
|           |          |                 |                 | 1.25          | 92   | 87  | 82  | 79  | 91  | 86   | 82  | 79  | 89  | 85  | 81   | 78  | 87  | 83  | 80 | 78   | 76 |    |    |      |     |
| 下方投影面積    |          | cm <sup>2</sup> | 1.5             | 95            | 90   | 86  | 83  | 94  | 89  | 85   | 83  | 92  | 88  | 85  | 82   | 90  | 86  | 84  | 81 | 80   |    |    |    |      |     |
| 等価発光面積    |          |                 | cm <sup>2</sup> | 2.0           | 98   | 94  | 91  | 88  | 97  | 93   | 90  | 88  | 95  | 92  | 89   | 87  | 93  | 90  | 88 | 86   | 84 |    |    |      |     |
| 取付高さ      | 器具間隔最大限  |                 |                 | 2.5           | 100  | 97  | 94  | 92  | 99  | 96   | 93  | 91  | 97  | 94  | 92   | 90  | 95  | 93  | 91 | 89   | 87 |    |    |      |     |
| 横方向 ( A ) |          | 縦方向 ( B )       |                 | 3.0           | 102  | 99  | 96  | 94  | 101 | 98   | 96  | 94  | 98  | 96  | 94   | 92  | 96  | 94  | 93 | 91   | 89 |    |    |      |     |
| H m       | 1.24 H m | 1.24 H m        | 4.0             | 103           | 101  | 99  | 97  | 102 | 100 | 98   | 97  | 100 | 98  | 97  | 95   | 98  | 96  | 95  | 94 | 92   |    |    |    |      |     |
|           |          |                 | 5.0             | 104           | 103  | 101 | 99  | 103 | 102 | 100  | 99  | 101 | 100 | 98  | 97   | 99  | 98  | 97  | 96 | 93   |    |    |    |      |     |
|           |          |                 | 7.0             | 106           | 104  | 103 | 102 | 104 | 103 | 102  | 101 | 102 | 101 | 100 | 99   | 100 | 99  | 98  | 98 | 95   |    |    |    |      |     |
|           |          |                 | 10.0            | 106           | 105  | 104 | 104 | 105 | 104 | 103  | 103 | 103 | 102 | 102 | 101  | 101 | 100 | 100 | 99 | 96   |    |    |    |      |     |

