

屋内照明器具特性	
品番 (品名)	XNN2561PW
光源	LED4000_85_1885 ×1 1885.0 lm
管理番号	K0190269 (0) DB 1
BZ分類	BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束				1 0 0 %																		
保守率		良 中 否	0 . 8 3	0 . 6	6 0	4 9	4 2	3 7	5 9	4 8	4 1	3 7	5 7	4 7	4 1	3 6	5 5	4 6	4 1	3 6	3 4	
			0 . 8 1	0 . 8	7 1	6 0	5 3	4 8	6 9	5 9	5 2	4 7	6 7	5 8	5 2	4 7	6 4	5 7	5 1	4 7	4 5	
			0 . 7 7	1 . 0	7 7	6 7	6 0	5 5	7 6	6 7	6 0	5 5	7 3	6 5	5 9	5 5	7 0	6 4	5 9	5 4	5 2	
				1 . 2 5	8 3	7 4	6 8	6 3	8 1	7 3	6 7	6 2	7 9	7 2	6 6	6 2	7 6	7 0	6 5	6 1	5 9	
下方投影面積		c m ²	1 . 5	8 7	7 9	7 3	6 8	8 5	7 8	7 2	6 8	8 2	7 6	7 1	6 7	8 0	7 4	7 0	6 6	6 4		
等価発光面積			c m ²	2 . 0	9 2	8 5	8 0	7 6	9 0	8 4	7 9	7 5	8 7	8 2	7 8	7 4	8 5	8 1	7 7	7 4	7 1	
取付高さ	器具間隔最大限		2 . 5	9 5	8 9	8 5	8 1	9 3	8 8	8 4	8 0	9 1	8 6	8 3	7 9	8 8	8 4	8 1	7 8	7 6		
	横方向 (A) 縦方向 (B)		3 . 0	9 7	9 2	8 8	8 5	9 6	9 1	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 4	8 2	7 9		
H m	1 . 1 9 H m	1 . 1 9 H m	4 . 0	1 0 0	9 6	9 3	9 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 1	8 9	8 7	8 4		
			5 . 0	1 0 2	9 8	9 6	9 3	1 0 0	9 7	9 5	9 2	9 8	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 7		
			7 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 7	9 6	9 4	9 3	9 0		
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 7	9 9	9 8	9 7	9 6	9 3		

