

| 屋内照明器具特性 |                                         |
|----------|-----------------------------------------|
| 品番 (品名)  | XND3569WV                               |
| 光源       | LED3500_80_3950 ×1 3950.0 lm            |
| 管理番号     | K0179659 ( 0 ) DB 1                     |
| BZ分類     | BZ2 / 0.9 / BZ1 / 3.5 / BZ2 / 8.5 / BZ1 |

| 器具効率           |                    | 100 %              | 反射率  | 天井                | 80 % |     |     |     |     | 70 % |     |     |     |     | 50 % |     |     |    |    | 30 % |     |  |  |  | 0 % |
|----------------|--------------------|--------------------|------|-------------------|------|-----|-----|-----|-----|------|-----|-----|-----|-----|------|-----|-----|----|----|------|-----|--|--|--|-----|
|                |                    |                    |      | 壁                 | 70   | 50  | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30   | 10  | 70  | 50 | 30 | 10   | 0 % |  |  |  |     |
|                |                    |                    |      | 床                 | 10 % |     |     |     |     | 10 % |     |     |     |     | 10 % |     |     |    |    | 10 % |     |  |  |  | 0 % |
| 上方光束<br>下方光束   |                    | 100 %              | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |     |     |     |      |     |     |     |     |      |     |     |    |    |      |     |  |  |  |     |
| 保守率            |                    | 良<br>中<br>否        | 0.76 | 0.6               | 71   | 62  | 56  | 52  | 70  | 61   | 56  | 52  | 68  | 60  | 55   | 52  | 66  | 59 | 55 | 51   | 50  |  |  |  |     |
|                |                    |                    | 0.72 | 0.8               | 80   | 72  | 66  | 62  | 79  | 71   | 66  | 62  | 77  | 70  | 66   | 62  | 75  | 69 | 65 | 62   | 60  |  |  |  |     |
|                |                    |                    | 0.64 | 1.0               | 86   | 79  | 73  | 70  | 85  | 78   | 73  | 69  | 82  | 77  | 72   | 69  | 80  | 76 | 72 | 69   | 67  |  |  |  |     |
|                |                    |                    | 0.64 | 1.25              | 90   | 84  | 80  | 76  | 89  | 84   | 79  | 76  | 87  | 82  | 78   | 75  | 85  | 81 | 77 | 75   | 73  |  |  |  |     |
| 下方投影面積         |                    | cm <sup>2</sup>    | 1.5  | 93                | 88   | 84  | 80  | 92  | 87  | 83   | 80  | 90  | 86  | 82  | 79   | 88  | 84  | 81 | 79 | 77   |     |  |  |  |     |
| 等価発光面積         |                    |                    | 2.0  | 97                | 93   | 89  | 86  | 96  | 92  | 89   | 86  | 94  | 90  | 87  | 85   | 92  | 89  | 86 | 84 | 82   |     |  |  |  |     |
| 取付<br>高さ       | 器具間隔最大限            |                    | 2.5  | 100               | 96   | 93  | 90  | 98  | 95  | 92   | 90  | 96  | 93  | 91  | 89   | 94  | 92  | 89 | 88 | 85   |     |  |  |  |     |
|                | 横方向 (A) 縦方向 (B)    |                    | 3.0  | 101               | 98   | 95  | 93  | 100 | 97  | 94   | 92  | 98  | 95  | 93  | 91   | 95  | 93  | 92 | 90 | 88   |     |  |  |  |     |
| H <sub>m</sub> | 1.30H <sub>m</sub> | 1.30H <sub>m</sub> | 4.0  | 103               | 100  | 98  | 96  | 102 | 99  | 97   | 96  | 99  | 98  | 96  | 94   | 97  | 96  | 94 | 93 | 91   |     |  |  |  |     |
|                |                    |                    | 5.0  | 104               | 102  | 100 | 99  | 103 | 101 | 99   | 98  | 101 | 99  | 98  | 96   | 98  | 97  | 96 | 95 | 92   |     |  |  |  |     |
|                |                    |                    | 7.0  | 105               | 104  | 102 | 101 | 104 | 103 | 101  | 100 | 102 | 101 | 100 | 99   | 100 | 99  | 98 | 97 | 94   |     |  |  |  |     |
|                |                    |                    | 10.0 | 106               | 105  | 104 | 103 | 105 | 104 | 103  | 102 | 103 | 102 | 101 | 100  | 101 | 100 | 99 | 99 | 96   |     |  |  |  |     |

