

屋内照明器具特性	
品番 (品名)	XND5 5 3 6 WN
光源	LED5000_80_5280 x1 5280.0 lm
管理番号	K0179576 (1) DB 1
BZ分類	BZ1 / 4.5 / BZ2 / 6.0 / BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		1 0 0 %																				
保守率		良	0 . 6	7 5	6 7	6 2	5 9	7 4	6 7	6 2	5 8	7 3	6 6	6 2	5 8	7 1	6 5	6 1	5 8	5 7		
		中	0 . 8	8 3	7 6	7 1	6 7	8 2	7 5	7 1	6 7	8 0	7 4	7 0	6 7	7 8	7 3	7 0	6 7	6 5		
		否	0 . 7 2	1 . 0	8 8	8 1	7 7	7 3	8 7	8 1	7 6	7 3	8 5	7 9	7 6	7 2	8 3	7 8	7 5	7 2	7 1	
			0 . 6 4	1 . 2 5	9 2	8 6	8 2	7 8	9 1	8 5	8 1	7 8	8 9	8 4	8 0	7 8	8 7	8 3	8 0	7 7	7 5	
下方投影面積		c m ²	1 . 5	9 4	8 9	8 5	8 2	9 3	8 9	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 6	8 3	8 1	7 9		
			2 . 0	9 8	9 4	9 0	8 7	9 7	9 3	9 0	8 7	9 5	9 1	8 8	8 6	9 2	9 0	8 7	8 5	8 3		
等価発光面積		c m ²	2 . 5	1 0 0	9 6	9 3	9 1	9 9	9 6	9 3	9 0	9 7	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 6		
			3 . 0	1 0 1	9 8	9 6	9 3	1 0 0	9 7	9 5	9 3	9 8	9 6	9 3	9 2	9 6	9 4	9 2	9 0	8 8		
H m	0 . 7 4 H m	0 . 7 4 H m	4 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 6	9 5	9 3	9 1		
			5 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3		
			7 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5		
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 9	9 6		

