

屋内照明器具特性

品番 (品名)	XS Z B 1 0 0 6 2														
光源	LLD2411LCB1 ×1 500.0 l m														
管理番号	K0193247 (3) DB 1														
B Z 分類	B Z 1 / 0.9 / B Z 2 / 2.8 / B Z 3														

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束	14 %	室指数	照明率 (X 0.01)																			Z C M
下方光束	73 %																					
保守率	良 中 否	0.63	0.6	59	51	46	43	57	50	46	42	54	48	44	42	52	47	43	41	38		
		0.6	0.8	65	58	53	50	64	57	52	49	60	55	51	48	57	52	49	46	44		
		0.56	1.0	70	63	58	54	68	61	57	54	64	59	55	52	60	56	53	50	47		
			1.25	73	67	63	59	71	66	61	58	67	62	59	56	63	60	57	54	51		
下方投影面積	c m ²	1.5	76	70	66	62	74	69	65	61	69	65	62	59	65	62	59	57	53			
		2.0	79	75	71	68	77	73	69	66	72	69	66	64	68	65	63	61	57			
取付高さ	器具間隔最大限		2.5	81	77	74	71	79	75	72	69	74	71	69	67	70	68	66	64	59		
	横方向 (A)	縦方向 (B)	3.0	83	79	76	74	80	77	74	72	76	73	71	69	71	69	67	66	61		
H m	0.77 H m	0.77 H m	4.0	85	82	79	77	82	80	77	75	77	75	73	72	73	71	70	68	63		
			5.0	86	84	81	79	83	81	79	77	79	77	75	74	74	73	71	70	64		
			7.0	87	86	84	82	85	83	82	80	80	79	77	76	75	74	73	72	66		
			10.0	88	87	86	85	86	85	83	82	81	80	79	78	76	75	75	74	68		

