

屋内照明器具特性	
品番 (品名)	X S Z B 1 0 0 6 3
光源	L L D 2 4 1 1 V C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 3 2 4 7 (3) D B 1
B Z 分類	B Z 1 / 0 . 9 / B Z 2 / 2 . 8 / B Z 3

器具効率		8 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 4 % 7 3 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	5 9	5 1	4 6	4 3	5 7	5 0	4 6	4 2	5 4	4 8	4 4	4 2	5 2	4 7	4 3	4 1	3 8	
			0 . 6	0 . 8	6 5	5 8	5 3	5 0	6 4	5 7	5 2	4 9	6 0	5 5	5 1	4 8	5 7	5 2	4 9	4 6	4 4	
			0 . 5 6	1 . 0	7 0	6 3	5 8	5 4	6 8	6 1	5 7	5 4	6 4	5 9	5 5	5 2	6 0	5 6	5 3	5 0	4 7	
				1 . 2 5	7 3	6 7	6 3	5 9	7 1	6 6	6 1	5 8	6 7	6 2	5 9	5 6	6 3	6 0	5 7	5 4	5 1	
下方投影面積		c m ²	1 . 5	7 6	7 0	6 6	6 2	7 4	6 9	6 5	6 1	6 9	6 5	6 2	5 9	6 5	6 2	5 9	5 7	5 3		
等価発光面積			c m ²	2 . 0	7 9	7 5	7 1	6 8	7 7	7 3	6 9	6 6	7 2	6 9	6 6	6 4	6 8	6 5	6 3	6 1	5 7	
				2 . 5	8 1	7 7	7 4	7 1	7 9	7 5	7 2	6 9	7 4	7 1	6 9	6 7	7 0	6 8	6 6	6 4	5 9	
取付 高さ	器具間隔最大限		3 . 0	8 3	7 9	7 6	7 4	8 0	7 7	7 4	7 2	7 6	7 3	7 1	6 9	7 1	6 9	6 7	6 6	6 1		
	横方向 (A) 縦方向 (B)		4 . 0	8 5	8 2	7 9	7 7	8 2	8 0	7 7	7 5	7 7	7 5	7 3	7 2	7 3	7 1	7 0	6 8	6 3		
H m	0 . 7 7 H m	0 . 7 7 H m	5 . 0	8 6	8 4	8 1	7 9	8 3	8 1	7 9	7 7	7 9	7 7	7 5	7 4	7 4	7 3	7 1	7 0	6 4		
			7 . 0	8 7	8 6	8 4	8 2	8 5	8 3	8 2	8 0	8 0	7 9	7 7	7 6	7 5	7 4	7 3	7 2	6 6		
			1 0 . 0	8 8	8 7	8 6	8 5	8 6	8 5	8 3	8 2	8 1	8 0	7 9	7 8	7 6	7 5	7 5	7 4	6 8		

