

屋内照明器具特性	
品番 (品名)	XS Z B 1 0 1 0 8
光源	LLD2401LCB1 ×1 500.0 lm
管理番号	K0193687 (0) DB 1
BZ分類	BZ4/0.7/BZ3/0.9/BZ4/6.0/BZ5

器具効率		8 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 3	4 3	3 7	3 3	5 1	4 2	3 6	3 2	4 8	4 1	3 5	3 2	4 5	3 9	3 4	3 1	2 8
			0 . 6	0 . 8	6 1	5 2	4 6	4 1	5 9	5 1	4 5	4 1	5 6	4 9	4 4	4 0	5 3	4 7	4 2	3 9	3 6
			0 . 5 6	1 . 0	6 7	5 8	5 2	4 8	6 5	5 7	5 1	4 7	6 1	5 4	4 9	4 6	5 7	5 2	4 8	4 4	4 1
				1 . 2 5	7 1	6 4	5 8	5 3	6 9	6 2	5 7	5 3	6 5	5 9	5 5	5 1	6 1	5 6	5 3	4 9	4 6
下方投影面積		c m ²		1 . 5	7 5	6 8	6 2	5 8	7 2	6 6	6 1	5 7	6 8	6 3	5 8	5 5	6 4	6 0	5 6	5 3	4 9
			等価発光面積	c m ²	2 . 0	7 9	7 3	6 8	6 4	7 7	7 1	6 7	6 3	7 2	6 8	6 4	6 1	6 8	6 4	6 1	5 9
取付高さ	器具間隔最大限			2 . 5	8 2	7 6	7 2	6 8	7 9	7 5	7 1	6 7	7 5	7 1	6 8	6 5	7 0	6 7	6 5	6 2	5 8
	横方向 (A) 縦方向 (B)			3 . 0	8 3	7 9	7 5	7 2	8 1	7 7	7 3	7 0	7 7	7 3	7 0	6 8	7 2	7 0	6 7	6 5	6 0
H m	1 . 0 5 H m	0 . 4 9 H m		4 . 0	8 6	8 2	7 9	7 6	8 3	8 0	7 7	7 5	7 9	7 6	7 4	7 2	7 5	7 2	7 0	6 9	6 4
				5 . 0	8 7	8 4	8 2	7 9	8 5	8 2	8 0	7 7	8 0	7 8	7 6	7 4	7 6	7 4	7 3	7 1	6 6
				7 . 0	8 9	8 7	8 5	8 3	8 7	8 5	8 3	8 1	8 2	8 0	7 9	7 7	7 8	7 6	7 5	7 4	6 9
				1 0 . 0	9 0	8 9	8 7	8 6	8 8	8 7	8 5	8 4	8 4	8 2	8 1	8 0	7 9	7 8	7 7	7 6	7 1

