

屋内照明器具特性	
品番 (品名)	XNN1567SN
光源	LED5000_85_1630 ×1 1630.0lm
管理番号	K0176641(0)DB1
BZ分類	BZ1

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 8 1	0 . 6	7 5	6 6	6 1	5 8	7 4	6 6	6 1	5 8	7 2	6 5	6 1	5 7	7 0	6 4	6 0	5 7	5 6
			0 . 7 7	0 . 8	8 4	7 7	7 2	6 8	8 3	7 6	7 2	6 8	8 1	7 5	7 1	6 8	7 9	7 4	7 0	6 8	6 6
			1 . 0	1 . 0	8 9	8 3	7 8	7 5	8 8	8 2	7 8	7 5	8 6	8 1	7 7	7 5	8 4	8 0	7 7	7 4	7 3
			0 . 6 8	1 . 2 5	9 3	8 8	8 4	8 1	9 2	8 7	8 3	8 0	9 0	8 6	8 3	8 0	8 8	8 5	8 2	7 9	7 8
下方投影面積		c m ²	1 . 5	9 6	9 1	8 7	8 4	9 4	9 0	8 7	8 4	9 2	8 9	8 6	8 3	9 1	8 7	8 5	8 3	8 1	
			2 . 0	9 9	9 5	9 2	9 0	9 8	9 4	9 1	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 7	8 6	
等価発光面積		c m ²	2 . 5	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 4	9 2	9 0	8 8	
			3 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	9 0	
H m	0 . 9 6 H m		0 . 9 6 H m	4 . 0	1 0 4	1 0 1	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 2
				5 . 0	1 0 4	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4
				7 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 9	9 8	9 5
				1 0 . 0	1 0 6	1 0 5	1 0 5	1 0 4	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 6

