

| 屋内照明器具特性 |                                |
|----------|--------------------------------|
| 品番 (品名)  | XND9 9 3 1 F S K               |
| 光源       | LED5000_80_13475 ×1 13475.0 lm |
| 管理番号     | K0189098 ( 0 ) D 1             |
| BZ分類     | BZ2/0.7/BZ1/1.8/BZ2/8.5/BZ1    |

| 器具効率         |          | 100 %           | 反射率             | 天井                 | 80 % |     |     |     |     | 70 % |     |     |     |     | 50 % |     |     |     |    | 30 % |     |  |  |  | 0 % |
|--------------|----------|-----------------|-----------------|--------------------|------|-----|-----|-----|-----|------|-----|-----|-----|-----|------|-----|-----|-----|----|------|-----|--|--|--|-----|
|              |          |                 |                 | 壁                  | 70   | 50  | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30   | 10  | 70  | 50  | 30 | 10   | 0 % |  |  |  |     |
|              |          |                 |                 | 床                  | 10 % |     |     |     |     | 10 % |     |     |     |     | 10 % |     |     |     |    | 10 % |     |  |  |  | 0 % |
| 上方光束<br>下方光束 |          | 100 %           | 室指数             | 照明率 ( X0.01 ) Z CM |      |     |     |     |     |      |     |     |     |     |      |     |     |     |    |      |     |  |  |  |     |
| 保守率          |          | 良<br>中<br>否     | 0.72            | 0.6                | 71   | 62  | 57  | 53  | 70  | 62   | 56  | 52  | 68  | 61  | 56   | 52  | 67  | 60  | 56 | 52   | 51  |  |  |  |     |
|              |          |                 | 0.68            | 0.8                | 80   | 72  | 67  | 63  | 79  | 72   | 67  | 63  | 77  | 71  | 66   | 63  | 75  | 70  | 65 | 62   | 61  |  |  |  |     |
|              |          |                 | 0.64            | 1.0                | 86   | 79  | 74  | 70  | 85  | 78   | 73  | 70  | 83  | 77  | 73   | 69  | 81  | 76  | 72 | 69   | 67  |  |  |  |     |
|              |          |                 |                 | 1.25               | 90   | 84  | 80  | 76  | 89  | 83   | 79  | 76  | 87  | 82  | 78   | 75  | 85  | 81  | 77 | 75   | 73  |  |  |  |     |
| 下方投影面積       |          | cm <sup>2</sup> | 1.5             | 93                 | 88   | 83  | 80  | 92  | 87  | 83   | 80  | 90  | 85  | 82  | 79   | 88  | 84  | 81  | 78 | 77   |     |  |  |  |     |
| 等価発光面積       |          |                 | cm <sup>2</sup> | 2.0                | 97   | 93  | 89  | 86  | 96  | 92   | 88  | 85  | 94  | 90  | 87   | 85  | 91  | 88  | 86 | 84   | 82  |  |  |  |     |
|              |          |                 |                 | 2.5                | 99   | 96  | 92  | 90  | 98  | 95   | 92  | 89  | 96  | 93  | 90   | 88  | 94  | 91  | 89 | 87   | 85  |  |  |  |     |
| 取付高さ         | 器具間隔最大限  |                 | 3.0             | 101                | 98   | 95  | 92  | 100 | 97  | 94   | 92  | 97  | 95  | 93  | 91   | 95  | 93  | 91  | 90 | 87   |     |  |  |  |     |
| H m          | 1.19 H m | 1.19 H m        |                 | 4.0                | 103  | 100 | 98  | 96  | 102 | 99   | 97  | 95  | 99  | 97  | 96   | 94  | 97  | 95  | 94 | 93   | 90  |  |  |  |     |
|              |          |                 |                 | 5.0                | 104  | 102 | 100 | 98  | 103 | 101  | 99  | 97  | 100 | 99  | 97   | 96  | 98  | 97  | 96 | 95   | 92  |  |  |  |     |
|              |          |                 |                 | 7.0                | 105  | 104 | 102 | 101 | 104 | 103  | 101 | 100 | 102 | 100 | 99   | 98  | 99  | 99  | 98 | 97   | 94  |  |  |  |     |
|              |          |                 |                 | 10.0               | 106  | 105 | 104 | 103 | 105 | 104  | 103 | 102 | 103 | 102 | 101  | 100 | 100 | 100 | 99 | 98   | 96  |  |  |  |     |
|              |          |                 |                 |                    |      |     |     |     |     |      |     |     |     |     |      |     |     |     |    |      |     |  |  |  |     |

