

屋内照明器具特性	
品番 (品名)	XND9 9 4 1 F S K
光源	LED5000_80_17250 ×1 17250.0 lm
管理番号	K0188314 (0) D 1
BZ分類	BZ2/0.7/BZ1/3.5/BZ2/8.5/BZ1

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
			室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 7 2	0 . 6	7 1	6 2	5 7	5 3	7 0	6 2	5 6	5 3	6 8	6 1	5 6	5 2	6 7	6 0	5 6	5 2	5 1
			0 . 6 8	0 . 8	8 0	7 2	6 7	6 3	7 9	7 2	6 7	6 3	7 7	7 1	6 6	6 3	7 5	7 0	6 6	6 2	6 1
			1 . 0	8 6	7 9	7 4	7 0	8 5	7 8	7 3	7 0	8 3	7 7	7 3	6 9	8 1	7 6	7 2	6 9	6 7	
			0 . 6 4	1 . 2 5	9 0	8 4	8 0	7 6	8 9	8 4	7 9	7 6	8 7	8 2	7 8	7 5	8 5	8 1	7 7	7 5	7 3
下方投影面積		c m ²	1 . 5	9 3	8 8	8 4	8 0	9 2	8 7	8 3	8 0	9 0	8 6	8 2	7 9	8 8	8 4	8 1	7 9	7 7	
等価発光面積			c m ²	2 . 0	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 6	9 4	9 0	8 7	8 5	9 1	8 9	8 6	8 4	8 2
				2 . 5	9 9	9 6	9 2	9 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 7	8 5
取付 高さ	器具間隔最大限		3 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7	
	横方向 (A) 縦方向 (B)			4 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 3	9 0
H m	1 . 1 9 H m 1 . 1 9 H m		5 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 2	
			7 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	9 9	9 8	9 9	9 9	9 8	9 7	9 4	
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 9	9 6	

